SPECIFICATION FOR APPROVAL

Customer :

Description : DC FAN

Customer Part No. NA REV. : 00

Delta Model No. : BSB0405HP-00 REV. : X01

Sample Issue No. :

Sample Issue Date : MAR. 20, 2023

PLEASE SEND ONE COPY OF THIS SPECIFICAITON BACK AFTER YOU SIGNED APPROVAL FOR PRODUCTION PRE-ARRANGMENT.

APPROVED BY:

DATE :

BSB0405HP-00 Delta Datasheet
sales@fansco.com
www.fansco.com

STATEMENT OF DEVIATION

■ NONE

□ DESCRIPTION:

Specification For Approval

Customer :

Description : DC FAN

Customer P/N :	NA	rev. :	00
Delta model no. :	BSB0405HP-00	Delta Safety Model No.:	BSB0405HP-00
Sample revision. :	X00	Issue no.:	
Sample issue date :	MAR. 20, 2023	Quant	ND3

1. SCOPE:
THIS SPECIFICATION DEFINES THE ELECTRICAL AND MECHANICAL CHARACTERISTICS OF THE DC BRUSHLESS BLOWER FLOW FAN.

2. CHARACTERS:

ITEM	DESCRIPTION
RATED VOLTAGE	5.0V
OPERATION VOLTAGE	2.5 - 5.5 VDC
INPUT CURRENT(AVG.) #	0.30 (MAX 0.5) A (SAFETY CURRENT ON LABEL : 0.50A)
INPUT POWER(AVG.)	1.5 (MAX 2.5) W
SPEED	11000±10%R.P.M.
MAX. AIR FLOW (AT ZERO STATIC PRESSURE)	2.32(MIN. 2.08) CFM
MAX. AIR PRESSURE (AT ZERO AIRFLOW)	27.3 (MIN. 22.3) mmH_2O
ACOUSTICAL NOISE (AVG.) TEST DISTANCE : 0.3M	43.7 (MAX. 46.3) dB-A
OPERATION DUTY CYCLE	20~100% (25K Hz)
INSULATION TYPE	UL: CLASS A
INSULATION STRENGT	10 MEG OHM MIN. AT 500 VDC (BETWEEN FRAME AND (+) TERMINAL)
DIELECTRIC STRENGTH	5 mA MAX. AT 500 VAC 50/60 Hz ONE MINUTE, (BETWEEN FRAME AND (+) TERMINAL)

THE MAX VALUE OF CONSUMING CURRENT DOES NOT REPRESENT THE PEAK VALUE, THE PEAK VALUE NEED MEASURE BY OSCILLOSCOPE.


PART NO: NA

DELTA MODEL: BSB0405HP-00

LIFE EXPECTANCE (L10) (AT LABEL VOLTAGE)	30,000 HOURS CONTINUOUS OPERATION AT 40 ° C WITH 15 ~ 65 %RH.
ROTATION	COUNTERCLOCKWISE VIEW FROM NAME PLATE SIDE
LOCKED PROTECTION	THE FAN WILL SHUT DOWN WHEN LOCKED ROTOR.

NOTES:

1. ALL READINGS ARE MEASURED AFTER STABLY WARMING UP THROUGH 10 MINUTES.
2. STANDARD AIR PROPERTY IS AIR AT (Td) ND35C04-XXXXX RELATIVE HUMIDITY , AND (Pb) 760 mmHg BAROMETRIC PRESSURE.
3. THE VALUES WRITTEN IN PARENS , ( ), ARE LIMITED SPEC.
4. ACOUSTICAL NOISE MEASURING CONDITION:



NOISE IS MEASURED AT RATED VOLTAGE IN FREE AIR IN ANECHOIC CHAMBER WITH B & K SOUND LEVEL METER WITH MICROPHONE AT A DISTANCE OF ONE METER FROM THE FAN INTAKE.

PART NO: NA

DELTA MODEL: BSB0405HP-00

3.MECHANICAL:

3-1. DIMENSIONS---------- SEE DIMENSIONS DRAWING
3-2. FRAME----------PLASTIC UL: 94V-0
3-3. IMPELLER---------- PLASTIC UL: 94V-0
3-4. PILLOW----------AL5052
3-5. BEARING SYSTEM----------SLEEVE
3-6. WEIGHT---------- 4.5 GRAMS(REF.)

4. ENVIRONMENTAL:

4-1. OPERATING TEMPERATURE---------- -10 TO +70 DEGREE C
4-2. STORAGE TEMPERATURE---------- -40 TO +75 DEGREE C
4-3. OPERATING HUMIDITY---------- 5 TO 90 % RH
4-4. STORAGE HUMIDITY---------- 5 TO 95 % RH

5. PROTECTION:

5-1. LOCKED ROTOR PROTECTION
IMPEDANCE OF MOTOR WINDING PROTECTS MOTOR FROM FIRE IN 96 HOURS OF LOCKED ROTOR CONDITION AT THE RATED VOLTAGE.

6. RE OZONE DEPLETING SUBSTANCES:


6-1. NO CONTAINING PBBs, PBBOs, CFCs, PBBEs, PBDPEs AND HCFCs.

7. PRODUCTION LOCATION

7-1. PRODUCTS WILL BE PRODUCED IN CHINA OR THAILAND.

PART NO:	NA
DELTA MODEL:	BSB0405HP-00

8. P & Q CURVE:




*TEST CONDITION: INPUT VOLTAGE-----OPERATION VOLTAGE
TEMPERATURE-----ROOM TEMPERATURE
HUMIDITY-----65%RH

*USE Pmax AND Qmax TO DRAW ABOVE CURVE.

PART NO:	NA
DELTA MODEL:	BSB0405HP-00

9. DIMENSION DRAWING:




NOTES :

1. HOUSING: ACES 50375-0041N-001 OR EQUIVALENT
2. LEAD WIRE: UL10064 AWG#32
   - PIN 1: BLACK WIRE ---- (-)
   - PIN 2: RED WIRE ---- (+)
   - PIN 3: YELLOW WIRE ---- (FG)
   - PIN 4: BLUE WIRE ---- (PWM)
3. THIS PRODUCT IS RoHS COMPLIANT.
4. UNIT:mm
5. THE SYMBOL "*" DENOTE IMPORTANT DIMENSION

10.FREQUENCY GENERATOR (FG) SIGNAL:

10-1. OUTPUT CIRCUIT - OPEN DRAIN MODE:



CAUTION:

THE FG SIGNAL LEAD WIRE MUST BE KEPT AWAY FROM "+" LEAD WIRE & "-" LEAD WIRE.


10-2. SPECIFICATION:

V_{FG}= 5V TYP. (VCC MAX.)

I_D = 5mA MAX. $R \geqq V_{FG} / I_D$

THE RESISTOR R IS NOT INCLUDED IN FAN CIRCUIT AND NEEDS TO BE PROVIDED BY FAN USER

10-3. FREQUENCY GENERATOR WAVEFORM:




N=R.P.M

TS=60/N(SEC)


BSB0405HP-00 Delta Datasheet FansCo sales@fansco.com www.fansco.com

11. PWM CONTROL FUNCTION

11-1. PWM CONTROL INTERFACE



SIGNAL VOLTAGE RANGE: 0 ~ (V_+ - 0.5) VDC



DUTY CYCLE= $\frac{t}{T}$ *100(%)

Frequency = $\frac{1}{T}$

- HIGH LEVEL : (V_+ - 0.5) VDC max.
  2.8 VDC min.
- LOW LEVEL : 0.6 VDC max.
  0 VDC min.
- R_{pu}: 200Kohm ~ 500Kohm.


- THE R_{pu} IS A SEMICONDUCTING RESISTOR BUILD IN THE IC WAFER OF THE FAN DRIVER FOR THE DEFAULT SETTING.
- THE FREQUENCY FOR CONTROL SINGAL OF THE FAN SHALL BE ABLE TO ACCEPT A 20KHZ~50KHZ.
- THE PREFERRED OPERATING FREQUENCY OF PWM SIGNAL IS 25KHz.
- AT 100% DUTY CYCLE, THE ROTOR WILL SPIN AT MAXIMUM SPEED.
- AT 0% DUTY CYCLE, THE ROTOR WILL STOP TO SPIN.
- DUE TO PULL UP RESISTER(R_{pu}), WHEN THE PWM CONTROL LEAD WIRE IS DISCONNECTED, THE ROTOR WILL SPIN AT MAXIMUM SPEED.

11-2. THE REQUIREMENT OF WAVEFORM QUALITY OF PWM SIGNAL

- THE RECOMMENDED PWM SIGNAL FROM SYSTEM IS TTL (t_r=50ns, t_f=50ns), EVEN IF THE PWM LEAD OF FAN IS DISCONNECTED.
- THE MAXIMUM PERMISSIBLE OF WAVEFORM DISTORTION:

V_{IH} : (V_+ - 0.5) × 90% RISE TIME : t_r<500ns

V_{IL} : (V_+ - 0.5) × 10% FALL TIME : t_f<500ns



11-3. FAN CHARACTERISTICS

TEST CONDITION : AT 25°C, V^+= 5.0VDC & PWM SIGNAL AS FOLLOW

DUTY CYCLE (%)	SPEED R.P.M.	CURRENT (A) TYP.
100	11000±10%	0.30(A)
0	0	0.2(mA)


* PWM SIGNAL
PWM FREQUENCY = 25 KHz



- MIN. STARTED DUTY CYCLE : 30%
  WHEN DUTY CYCLE IS SET FOR MORE THAN 30% , THE FAN WILL BE ABLE TO START FROM A DEAD STOP.


BSB0405HP-00 Delta Datasheet FansCo sales@fansco.com www.fansco.com

12. TYPICAL STARTUP SEQUENCE (CONDITION: 25°C, 5.0VDC, 1 ATM)



- THE FIRST 100mS IS USED TO WAIT FOR VCC SETTLING.
- THE PWM SIGNAL CAN NOT INPUT BEFORE VCC.

13. DEFINITION OF LOCK DETECTION, LOCK-OFF TIME, AND QUICK START FUNCTION



A* : TYPICALLY 1.0 SEC FOR LOCK DETECTION.

B* : COMMONLY 100mS DETECTION TIME FOR LOCK-OFF RELEASE.

C* : FG OUTPUT DELAY TIME.


- THE 5SEC LOCK-OFF TIME IS ALSO A TYPICAL VALUE AND THE MAXIMUM TOLERANCE IS 10 SECONDS.

BSB0405HP-00 Delta Datasheet FansCo sales@fansco.com www.fansco.com


PART NO:	NA
DELTA MODEL:	BSB0405HP-00

14. Safety notice

DON'T PRESS BLADE OR HUB




DON'T HIT&PRESS FAN BASE



DON'T PULL CABLE



DON'T PULL OUT BLADE



Application Notice

1. Delta will not guarantee the performance of the products if the application condition falls outside the parameters set forth in the specification.
2. A written request should be submitted to Delta prior to approval if deviation from this specification is required.
3. Please exercise caution when handling fans. Damage may be caused when pressure is applied to the impeller, if the fans are handled by the lead wires, or if the fan was hard-dropped to the production floor.
4. Except as pertains to some special designs, there is no guarantee that the products will be free from any such safety problems or failures as caused by the introduction of powder, droplets of water or encroachment of insect into the hub.
5. The above-mentioned conditions are representative of some unique examples and viewed as the first point of reference prior to all other information.
6. It is very important to establish the correct polarity before connecting the fan to the power source. Positive (+) and Negative (-). Damage may be caused to the fans if connection is with reverse polarity, if there is no foolproof method to protect against such error specifically mentioned in this spec.
7. Delta fans without special protection are not suitable where any corrosive fluids are introduced to their environment.
8. Please ensure all fans are stored according to the storage temperature limits specified. Do not store fans in a high humidity environment. We highly recommend performance testing is conducted before shipping, if the fans have been stored over 6 months.
9. Not all fans are provided with the Lock Rotor Protection feature. If you impair the rotation of the impeller for the fans that do not have this function, the performance of those fans will lead to failure.
10. Please be cautious when mounting the fan. Incorrect mounting of fans may cause excess resonance, vibration and subsequent noise.
11. It is important to consider safety when testing the fans. A suitable fan guard should be fitted to the fan to guard against any potential for personal injury.
12. Except where specifically stated, all tests are carried out at room (ambient) temperature and relative humidity conditions of 25°C, 65% RH. The test value is only for fan performance itself.
13. Be certain to connect an " 4.7μF or greater" capacitor to the fan externally when the application calls for using multiple fans in parallel, to avoid any unstable power.

BSB0405HP-00 Delta Datasheet FansCo sales@fansco.com www.fansco.com