



3412 NGHH-508

3412NGHH-508 (9292506508) ebmpapst Datasheet FansCo  
sales@fansco.com  
www.fansco.com

Customer specification: No  
Version: 1.0  
Created: 30.06.2011

**INDEX**

<b>1</b>	<b>General .....</b>	<b>2</b>
<b>2</b>	<b>Mechanics .....</b>	<b>2</b>
2.1	General.....	2
2.2	Motor .....	2
2.3	Connections .....	3
<b>3</b>	<b>Operating Data.....</b>	<b>4</b>
3.1	Operating Data - Electrical Interface - Input.....	4
3.2	Electrical Operating Data .....	4
3.3	Operating Data - Electrical Interface -Output .....	4
3.4	Electrical Features.....	5
3.5	Aerodynamic .....	5
3.6	Sound Data .....	5
<b>4</b>	<b>Environment.....</b>	<b>6</b>
4.1	General.....	6
4.2	Climatic requirements.....	6
4.3	Mechanical requirements .....	7
4.4	EMC.....	7
<b>5</b>	<b>Safety.....</b>	<b>7</b>
5.1	Electrical Safety.....	7
5.2	Approval Tests .....	7
<b>6</b>	<b>Reliability.....</b>	<b>7</b>
6.1	General.....	7
6.2	Additional Data .....	7

**Special features according to QMH 2-5.4.7 and company standard 1-23.00 have the following definitions:**

**"A"** : Product features or process parameters which influence the safety of a product or the compliance of legal requirements. (Must not necessary verified and documented 100%. Standards and legal requirements must be considered.)

**"FK"** : Product features or process parameters which influence the fit and function of a product or which have to be controlled or documented for some other reasons (e.g. Customer requirements).

**General**


Fan type	Fan	
Rotational direction looking at rotor	counterclockwise	<b>FK</b>
Airflow direction	Air outlet over struts	<b>FK</b>
Bearing system	Sleeve bearing	
Lubrication	see sectional drawing of the bearing	
Mounting position	any	
Tolerance		
Balancing grade	16,0	<b>FK</b>
Impeller weight	36,0 g	

**Mechanics****General**

Width	92,0 mm	
Height	92,0 mm	
Depth	25,4 mm	
Diameter	0,0 mm	
Weight	0,106 kg	
Housing material	Plastic	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges	wire outlet corner: 40 Ncm remaining corners: 60 Ncm	
Screw size	ISO 4762 - M4 degreased, without an additional brace and without washer	

**Motor**

Type of motor	Electronically commutated external rotor	
Diameter of the motor	25,0 mm	
Height of the motor	6,0 mm	
Number of phases	1	
Number of windings	1	
Operating mode	Continuous duty	
Insulation material class	E	



### Connections

Electrical connection	Wires - Plug	
Length of lead wire	270 mm	
Tolerance	+ - 10,0 mm	
Length of tube		
Tolerance	+ - 210 mm	
Wire gauge (AWG)	22	
Insulation diameter	1,70 mm	
Plug	see drawing	
Contact	see drawing	



	Colour	Operation
Wire 1	red	+ UB
Wire 2	blue	- GND

**Operating Data****Operating Data - Electrical Interface - Input**

Control input	None
---------------	------

**Electrical Operating Data**

Measurement conditions: Normal air density = 1,2 kg/m<sup>3</sup>; Temperature 23°C +/- 3°C; Motor axis horizontal; warm-up time before measuring 5 minutes (unless otherwise specified). In the intake and outlet area should not be any solid obstruction within 0,5 m.

$\Delta p = 0$ : corresp. to free air flow (see section 3.5)

I: corresp. to arithm. mean current value

Features	Condition	Symbol	Values		
Voltage range	$\Delta p = 0$	U	8,0 V		13,2 V
Nominal voltage	$\Delta p = 0$	$U_N$		12,0 V	
Power consumption	$\Delta p = 0$	P	1,2 W	3,2 W	4,2 W
Tolerance	0001		+/- 17,5 %	+/- 12,5 %	+/- 15,0 %
Current consumption	$\Delta p = 0$	I	155 mA	270 mA*)	320 mA
Tolerance	0001		+/- 17,5 %	+/- 12,5 %	+/- 15,0 %
Speed	$\Delta p = 0$	n	2.150 1/min	3.250 1/min*)	3.600 1/min
Tolerance	0001		+/- 12,5 %	+/- 7,5 %	+/- 10,0 %
Starting current consumption				910 mA	

\*) Attention: Marked values are "FK" features

**Operating Data - Electrical Interface -Output**


Tacho type	None
------------	------

Alarm type	None
------------	------



## Electrical Features

Electronic function	None	
Reversed polarity protection	Rectifying diode	<b>A</b>
Max. residual current at $U_n$	$I_F \leq 5 \mu A$	
Locked rotor protection	Auto restart	<b>A</b>
Locked rotor current at $U_n$	approx. 910 mA	
Clock signal $t_3/t_4$ at locked rotor	Typical: 0,2 s / 1,1 s $t_3$ : 0,06 s... 0,77 s $t_4$ : 0,3 s... 3,6 s	



## Aerodynamic

Measurement conditions: Measured with a double chamber intake rig acc. to DIN EN ISO 5801.  
Normal air density = 1,2 kg/m<sup>3</sup>; Temperature 23°C +/- 3°C;  
In the intake and outlet area should not be any solid obstruction within 0,5 m.

a.) Operation condition:

3.250 1/min at free air flow

Max. free-air flow ( $\Delta p = 0 / \dot{V} = \max.$ )	100,0 m <sup>3</sup> /h	<b>FK</b>
Max. static pressure ( $\Delta p = \max. / \dot{V} = 0$ )	50 Pa	<b>FK</b>

## Sound Data

Measurement conditions: Sound pressure level: 1 Meter distance between microphone and the air intake.  
Sound power level: Acc. to DIN 45635 part 38 (ISO 10302)  
Measured in a semianchoic chamber with a background noise level of  $L_p(A) < 5 \text{ dB}(A)$   
For further measurement conditions see section 3.5

a.) Operation condition:

3.250 1/min at free air flow



Optimal operating point	68,0 m <sup>3</sup> /h @ 18,0 Pa	
Sound power level at the optimal operating point	5,1 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	38,0 dB(A)	

## Environment

### General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	60 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

### Climatic requirements\*)

Humidity requirements	humid heat, constant; according to DIN EN 60068-2-78, 14 days	
Water exposure	None	
Radiation exposure	None	
Dust requirements	None	
Salt fog requirements	None	
Harmful gas requirements	None	

\*) Permitted application area:

The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoided.

Pollution degree 1 (according DIN EN 60664-1)

There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.

**Mechanical requirements**

Please require severity levels and specification parameters from the responsible development departments

**EMC**

not specified

**Safety****Electrical Safety**

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	Not applicable  Not applicable	A
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Air and leakage distances	1,0 mm / 1,2 mm	
Protection class	III	

**Approval Tests**

CE	Yes
UL	Yes
VDE	Yes
CSA	Yes
CCC	No

The approval tests are observed to:

U approval max.:13,2 V @ TU approval max.: 60 °C

**Reliability****General**

Life expectancy L10 at TU = 40 °C	70.000 h	
Life expectancy L10 at TU max.	45.000 h	

**Additional Data**



not specified