

Product Data Sheet

9693530230
VWC0119AUGBS
4414 HTR

ebmpapst

The engineer's choice

4414HTR (9693530230) ebmpapst Datasheet
sales@fansco.com
www.fansco.com



4414 HTR

INDEX

1 General 3

2 Mechanics 3

2.1 General..... 3

2.2 Connections..... 3

3 Operating Data 4

3.1 Electrical Interface - Input..... 4

3.2 Electrical Operating Data 5

3.3 Electrical Features 6

3.4 Aerodynamics 6

3.5 Sound Data..... 7

4 Environment..... 7

4.1 General..... 7

4.2 Climatic Requirements 7

5 Safety..... 8

5.1 Electrical Safety 8

5.2 Approval Tests 8

6 Reliability..... 8

6.1 General..... 8

1 General

Fan type	Fan	
Rotating direction looking at rotor	Clockwise	
Airflow direction	Air outlet over struts	
Bearing system	Ball bearing	
Mounting position - shaft	Any	


2 Mechanics

2.1 General

Width	119,0 mm	
Height	119,0 mm	
Depth	38,0 mm	
Mass	0,305 kg	
Housing material	Plastic	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges	Wire outlet corner: 80 Ncm Remaining corners: 80 Ncm	
Screw size	ISO 4762 - M4 degreased, without an additional brace and without washer	

2.2 Connections

Electrical connection	Wires	
Lead wire length	L = 310 mm	
Tolerance	+/- 10 mm	
Wire size (AWG)	24	
Insulation diameter	1,10 mm	




Wire	Color	Operation
1	red	+ UB
2	blue	- GND
3	white	NTC
4	black	- GND NTC

3 Operating Data

3.1 Electrical Interface - Input

Control input	External Temperature Sensor
---------------	-----------------------------

Features



3.2 Electrical Operating Data

Measurement conditions: Normal air density = 1,2 kg/m³; Temperature 23°C +/- 3°C; Motor axis horizontal; warm-up time before measuring 5 minutes (unless otherwise specified). In the intake and outlet area should not be any solid obstruction within 0,5 m.


$\Delta p = 0$: corresp. to free air flow (see chapter aerodynamics)
I: corresp. to arithm. mean current value

Name	Condition		
TU 0001	TU: > 35 °C		
NTC 0001	NTC 62 kOhm		

Features	Condition	Symbol	Values		
Voltage range		U	20,4 V		26,4 V
Nominal voltage		U _N		24,0 V	
Power consumption	$\Delta p = 0$	P	5,1 W +- 17,5 %	7,6 W +- 25,0 %	7,5 W +- 25,0 %
Tolerance	TU / NTC 0010				
Current consumption	$\Delta p = 0$	I	250 mA +- 17,5 %	315 mA +- 25,0 %	285 mA +- 25,0 %
Tolerance	TU / NTC 0010				
Speed	$\Delta p = 0$	n	3.800 1/min +- 12,5 %	4.300 1/min +- 6,0 %	4.300 1/min +- 6,0 %
Tolerance	TU / NTC 0010				
Starting current consumption				< 2.350 mA	

3.3 Electrical Features

Electronic function	Speed-Controlled	
Reversed polarity protection	Rectifying diode	
Max. residual current at U_N	$I_F < 1 \text{ mA}$	
Locked rotor protection	Auto restart	
Locked rotor current at U_N	I_{block} approx. 2.150 mA	
Clock signal at locked rotor	t_3 / t_4 typical: 0,4 s / 20 s	



3.4 Aerodynamics

Measurement conditions: Measured with a double chamber intake rig acc. to DIN EN ISO 5801. Normal air density = 1,2 kg/m³; Temperature 23°C +/- 3°C; In the intake and outlet area should not be any solid obstruction within 0,5 m. Motor shaft horizontal. The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions.

a.) Operation condition:

at free air flow		
Max. free-air flow ($\Delta p = 0 / \dot{V} = \text{max.}$)	240 m ³ /h	
Max. static pressure ($\Delta p = \text{max.} / \dot{V} = 0$)	160 Pa	

3.5 Sound Data

Measurement conditions: Sound pressure level: 1 meter distance between microphone and the air intake.
Sound power level: Acc. to DIN 45635 part 38 (ISO 10302)
Measured in a semianchoic chamber with a background noise level of $L_p(A) < 5 \text{ dB(A)}$
For further measurement conditions see chapter aerodynamics.

a.) Operation condition:

at free air flow	
------------------	--

Optimal operating point		
Sound power level at the optimal operating point	6 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	50 dB(A)	

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	70 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic Requirements

Humidity requirements	humid heat, cyclic; according to DIN EN 60068-2-30, 6 cycle	
Water exposure	None	
Dust requirements	Dust check; according to DIN EN 60068-2-68, 6g/m ² d, 1 day	
Salt fog requirements	None	

Permitted application area:

The product is for the use in sheltered rooms with limited controlled temperature. Occasionally condensed water is allowed. Direct exposure to water must be avoided. Saline ambient conditions must be avoided.

Pollution degree 2 (according DIN EN 60664-1)

It occurs only non-conductive pollution. Occasionally, temporary conductivity caused by condensation occurs.

Please require severity levels and specification parameters from the responsible development departments.

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground.	500 VAC / 1 Min.	
B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	850 VDC / 1 Sec.	
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Clearance / creepage distance	1,0 mm / 1,2 mm	
Protection class	III	


5.2 Approval Tests

CE	EC Declaration of Conformity	Yes
EAC	Eurasian Conformity	Yes
UL	Underwriters Laboratories	Yes / UL507, Electric Fans E38324
VDE	Association for Electrical, Electronic and Information Technologies	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment
CSA	Canadian Standards Association	Yes / C22.2 No. 113 Fans and Ventilators
CCC	China Compulsory Certification	Not applicable

6 Reliability

6.1 General

Life expectancy L10 at TU = 40 °C	57.500 h	
Life expectancy L10 at TU max.	27.500 h	
Life expectancy L10 acc. to IPC 9591 at TU = 40 °C	97.500 h	



Zeichnung entspricht 3D-Modell:
Drawing is equivalent to 3D-Model:
9293510500_CPA_000_A

- 1.) Maße fuer Montageausschnitt
- max. Anzieldrehmoment = 0.8Nm
 - Axialspiel: mit Feder spielfrei verspannt
 - Anzahl und Länge der Litzen siehe BV- Bl. 1
- 1.) measures for mounting cut-out
- max. tightening torque = 0.8Nm
 - without axial clearance by a pre-loaded spring
 - length and number of wires see design specification page 1

AP-Referenzcode	AP-Teilenummer / Part No.	AP-Systemversion / AP-System Version	AP-Modell / AP-Model	AP-Produktname / AP-Product Name	AP-Produkttyp / AP-Product Type	AP-Produktfamilie / AP-Product Family	AP-Produktserie / AP-Product Series	AP-Produktvariante / AP-Product Variant	AP-Produktbeschreibung / AP-Product Description	AP-Produktstatus / AP-Product Status	AP-Produktversion / AP-Product Version	AP-Produkttyp / AP-Product Type	AP-Produktfamilie / AP-Product Family	AP-Produktserie / AP-Product Series	AP-Produktvariante / AP-Product Variant	AP-Produktbeschreibung / AP-Product Description	AP-Produktstatus / AP-Product Status	AP-Produktversion / AP-Product Version
<p>AP-Produktname / AP-Product Name: ebmpapst</p> <p>AP-Produkttyp / AP-Product Type: ebmpapst</p> <p>AP-Produktfamilie / AP-Product Family: ebmpapst</p> <p>AP-Produktserie / AP-Product Series: ebmpapst</p> <p>AP-Produktvariante / AP-Product Variant: ebmpapst</p> <p>AP-Produktbeschreibung / AP-Product Description: ebmpapst</p> <p>AP-Produktstatus / AP-Product Status: ebmpapst</p> <p>AP-Produktversion / AP-Product Version: ebmpapst</p> <p>AP-Produkttyp / AP-Product Type: ebmpapst</p> <p>AP-Produktfamilie / AP-Product Family: ebmpapst</p> <p>AP-Produktserie / AP-Product Series: ebmpapst</p> <p>AP-Produktvariante / AP-Product Variant: ebmpapst</p> <p>AP-Produktbeschreibung / AP-Product Description: ebmpapst</p> <p>AP-Produktstatus / AP-Product Status: ebmpapst</p> <p>AP-Produktversion / AP-Product Version: ebmpapst</p>																		

Copyright of this document, and giving it others and the use or communication of the contents thereof, are prohibited without express authority. Owners are liable to the patent of design. All rights are reserved.

Rechtlich geschützt nach DIN ISO 9001:2015