

**ebm-papst St. Georgen GmbH & Co. KG**

Hermann-Papst-Str. 1

D-78112 St. Georgen

Phone +49 (0) 7724 81-0

Fax +49 (0) 7724 81-1309

sales@fansco.com

www.fansco.com

**Nominal data**

| Type                     | 612 F-637         |              |
|--------------------------|-------------------|--------------|
| Nominal voltage          | VDC               | 12           |
| Nominal voltage range    | VDC               | 10.8 .. 12.6 |
| Speed (rpm)              | min <sup>-1</sup> | 3900         |
| Power consumption        | W                 | 1            |
| Min. ambient temperature | °C                | -20          |
| Max. ambient temperature | °C                | 80           |
| Air flow                 | m <sup>3</sup> /h | 29           |
| Sound power level        | B                 | 4.4          |
| Sound pressure level     | dB(A)             | 27           |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change




**Technical description**

|                                  |                                                                                                          |
|----------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>Weight</b>                    | 0.030 kg                                                                                                 |
| <b>Dimensions</b>                | 60 x 60 x 15 mm                                                                                          |
| <b>Impeller material</b>         | Glass-fiber reinforced PA plastic                                                                        |
| <b>Housing material</b>          | Glass-fiber reinforced PBT plastic                                                                       |
| <b>Airflow direction</b>         | Exhaust over struts                                                                                      |
| <b>Direction of rotation</b>     | Counterclockwise, viewed toward rotor                                                                    |
| <b>Storage</b>                   | Sintec sleeve bearing                                                                                    |
| <b>Service life L10 at 20 °C</b> | 50000 h                                                                                                  |
| <b>Service life L10 at 60 °C</b> | 20000 h                                                                                                  |
| <b>Cable</b>                     | Leads AWG 28, TR 64, stripped and tin-plated.                                                            |
| <b>Motor protection</b>          | Protection against reverse polarity and blocked rotor.                                                   |
| <b>Option</b>                    | Possible custom designs:<br>Speed signal<br>Go / No-go alarm<br>PWM control input<br>Moisture protection |



## Product drawing



## Curves: Air performance

