

8300100038
VBS0450CTTLS

EC centrifugal fan - RadiPac

backward-curved, single-intake

ebm-papst Mulfingen GmbH & Co. KGaA & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
info1@de.fansco.com
www.fansco.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300100038	
Motor	E15031-55	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2960
Power consumption	W	4000
Current draw	A	6.0
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	71.6	57.8	09 Power consumption P_{ed}	kW	3.94
02 Measurement category		A		09 Air flow q_v	m³/h	8540
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	1145
04 Efficiency grade N		75.8	62	10 Speed (rpm) n	min ⁻¹	2955
05 Variable speed drive		Yes		11 Specific ratio*		1.01

Data obtained at optimum efficiency level.
The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

* Specific ratio = $1 + p_b / 100\,000\text{ Pa}$ LU-228317

Technical description

Weight	19.22 kg
Size	450 mm
Motor size	150
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Number of blades	5
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.3 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection - Vibration sensor
Power Factor Correction (PFC)	Passive (through low-capacitance DC link)
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Electronic motor protection
Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.

8300100038
VBS0450CTTLS

EC centrifugal fan - RadiPac

backward-curved, single-intake


Conformity with standards	EN 61800-5-1; CE; UKCA
Approval	CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC; UL 1004-7 + 60730-1

8300100038
VBS0450CTTLS

EC centrifugal fan - RadiPac

backward-curved, single-intake

Product drawing




1	Accessory part: Inlet ring 8217102239 with pressure tap (k-factor: 232) (not included in scope of delivery)
2	Max. clearance for screw 20 mm
3	Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm (The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted)
4	Tightening torque 1.5 ± 0.2 Nm

8300100038
VBS0450CTTLS

EC centrifugal fan - RadiPac

backward-curved, single-intake

Accessory part




Inlet ring 8217102239 with pressure tap (k-factor: 232)

- | | |
|---|--|
| 1 | Fastening holes for FlowGrid 35505-2-2957 (not included in scope of delivery) are provided and must be subsequently opened as required |
|---|--|

EC centrifugal fan - RadiPac

backward-curved, single-intake

Connection diagram




No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V/PWM, Ri=100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Actual speed Characteristic curve parametrizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

Terminal/plug assignment

configurable option		For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.3		configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification	configurable IO mode	CON2	inverse																									
									INPUT													OUTPUT												
IO1	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D158 [0]	○	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: fan modulation level %	D130 [11]	signal: actual speed	D130 [12]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [4]	pulse output for auto-addressing	D130 [1]																	
	○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D158 [2]	○	switch: set value source	(selected directly via IO mode)	D130 [0]	signal: tach out	D16A [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D101 [...]																	
	○ Tach out (open collector output)	U _{max} = 50VDC, I _{max} = 20mA, SELV	D158 [5]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ Diagnostics out (open collector output)	U _{max} = 50VDC, I _{max} = 20mA, SELV	D158 [6]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
IO2	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [0]	○	switch: control function: heating (pos.) / cooling (neg.)	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [2]	○	switch: parameter set: #1 / #2	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV	D159 [3]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [0]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
IO3	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ PWMIn3: digital input, idle level high	PWM = 40Hz - 10KHz, characteristics parameterizable	D15A [7]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ PWMIn3: digital input, idle level low	active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ Aout3 0-10V: analog output	active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
RSA RSB	○ Tacho out (pulses), analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ Diagnostics out (pulses)	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ Diagnostics out (pulses)	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ Diagnostics out (pulses)	MODBUS RTU, specification V6.3, SELV	D15A [6]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
Vout	○ voltage output	MODBUS RTU, specification V6.3, SELV	D16E [...]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																
	○ alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	voltage parameterizable 3.3..24VDC +/- 5%, P _{max} =800mW, short-circuit-proof, supply for external devices, SELV 15...50VDC	D16E [...]	○	switch: tach out	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [11]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	signal: tach out	D16A [...]	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]																

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-228317-1
Date: 2023-08-04
Nozzle: 8217101922

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	LwA	q _V	P _{fs}	q _V	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	dB	m³/h	Pa	cfm	in. wg
1	3~	400	50	2960	2637	4.08	86	94	98	100	12690	0	7470	0.00
2	3~	400	50	2960	3469	5.31	81	88	93	94	11235	600	6615	2.41
3	3~	400	50	2960	4000	6.00	74	83	90	91	8185	1200	4820	4.82
4	3~	400	50	2960	3693	5.65	79	87	93	94	5020	1550	2955	6.22
5	3~	400	50	2390	1429	2.32	82	90	93	95	10305	0	6065	0.00
6	3~	400	50	2395	1864	2.93	76	83	88	89	9070	393	5335	1.58
7	3~	400	50	2390	2113	3.30	69	77	85	86	6620	785	3895	3.15
8	3~	400	50	2390	2005	3.15	73	80	87	88	4070	1025	2395	4.11
9	3~	400	50	1790	665	1.26	74	83	87	88	7680	0	4520	0.00
10	3~	400	50	1790	847	1.49	68	77	81	83	6755	219	3975	0.88
11	3~	400	50	1795	944	1.63	62	70	77	78	4960	441	2920	1.77
12	3~	400	50	1790	899	1.56	64	72	78	79	3050	577	1795	2.32
13	3~	400	50	1195	247	0.65	64	73	77	78	5065	0	2980	0.00
14	3~	400	50	1195	298	0.73	58	67	71	73	4460	95	2625	0.38
15	3~	400	50	1195	327	0.78	52	61	67	68	3295	195	1940	0.78
16	3~	400	50	1195	315	0.77	52	60	66	67	2035	256	1200	1.03

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_V = Air flow · P_{fs} = Pressure increase