

8300100204
VBF0800XTXNS

EC centrifugal module

backward-curved, single-intake
with cube design

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300100204	
Motor	E28001-80	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Status		prelim.
Speed (rpm)	min ⁻¹	1750
Power consumption	W	24500
Current draw	A	38.5
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	35

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	68.7	62.9	09 Power consumption P_{ed}	kW	24.38
02 Measurement category		A		09 Air flow q_v	m ³ /h	28220
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	2075
04 Efficiency grade N		67.8	62	10 Speed (rpm) n	min ⁻¹	1740
05 Variable speed drive		Yes		11 Specific ratio [*]		1.02

Data obtained at optimum efficiency level.

^{*} Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-223060

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).



8300100204

VBF0800TXNS

EC centrifugal module

backward-curved, single-intake

with cube design

Technical description

Size	800 mm
Motor size	280
Rotor surface	Unpainted
Electronics housing material	Die-cast aluminum
Impeller material	Sheet aluminum
Support plate material	Sheet steel, galvanized
Spacer material	Aluminum
Inlet nozzle material	Sheet steel, galvanized
Guard grille material	Steel, coated with white-aluminum plastic (RAL 9006)
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP50
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	See legend on product drawing
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Hybrid bearing
Technical features	<ul style="list-style-type: none"> - Operation and alarm display with LED - Locked-rotor detection - Speed control - External 15-50 VDC input (parameterization) - Alarm relay - Configurable inputs/outputs (I/O) - Power limiter - MODBUS V7.0 - Motor current limitation - Soft start - Control interface with SELV potential safely disconnected from the mains - Temperature derating - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Protection class assignment	I; If a protective earth is connected by the customer This component for installation may have several local protection classes. This information relates to this component's basic design. The final protection class is based on the component's intended installation and connection.
Conformity with standards	EN 61800-5-1; CE



8300100204






VBF0800TXNS

EC centrifugal module

backward-curved, single-intake

with cube design

Product drawing




1	Inlet ring with pressure tap (k-factor: 695)
2	Mounting position for vibration-absorbing elements, tightening torque max. 20 Nm
3	Cable diameter min. 16 mm, max. 20.5 mm, tightening torque 6 ± 0.9 Nm
4	Cable diameter min. 5 mm, max. 13 mm, tightening torque 4 ± 0.6 Nm
5	Tightening torque 3.5 ± 0.5 Nm
6	Additional ground connection point. Tapping hole prepared for self-tapping M5 screw, max. screw-in depth 8 mm
7	Motor support structure
Installation position: Only base mounting, shaft horizontal (the struts next to the motor support plate must be vertical!)	
The drawing is only for showing the dimensions.	
The views do not represent the possible installation positions.	



EC centrifugal module

backward-curved, single-intake
with cube design

Connection diagram



No.	Conn.	Designation	Function/assignment
X1	PWR	PE	Protective earth
X1	PWR	L1, L2, L3	Power supply, phase, see nameplate for voltage range
X2	CTRL	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
X2	CTRL	NC	Status relay, floating status contact, break for failure
X10	CTRL	GND	Reference ground for control interface, SELV
X10	CTRL	Vout	Voltage output 3.3-24 VDC +/-5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
X10	CTRL	IO1	Factory setting: Analog input 0-10 V / PWM, Ri=100 kΩ, function: set value Characteristic curve parameterizable (see input characteristic curve "Input curve 1"), SELV Function parameterizable at the factory (see table Optional interface functions)
X10	CTRL	IO2	Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled" function parameterizable (see table Optional interface functions)
X10	CTRL	IO3	Factory settings: Analog output 0-10 V, max. 5mA, function: Fan speed Characteristic curve parameterizable (see output characteristic curve "Output curve 1"), SELV Function parameterizable at the factory (see table Optional interface functions)
X10	CTRL	RSA	RS-485 interface for MODBUS RSA, SELV dielectric strength to MODBUS RSB +/-14 V, dielectric strength to GND +/-7 V
X10	CTRL	RSB	RS-485 interface for MODBUS RSB, SELV dielectric strength to MODBUS RSA +/-14 V, dielectric strength to GND +/-7 V
		LED	green: status = good, ready for operation orange: status = warning red: status = failure



Terminal/plug assignment

IO	IO mode configuration	electrical specification	configurable IO mode	MODEBUS Register for IO mode configuration	INPUT	OUTPUT
IO1	◦ DIn1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5 VDC SELV	◦ DIn1 (active high): digital input	D158 [0]		
	◦ DIn1 (active low): digital input	active: applied voltage < 1.5 VDC, SELV not active: pin open or applied voltage 3.5-50 VDC SELV	◦ DIn1 (active low): digital input	D158 [1]		
	◦ Ain1 0-10 V/PWM: analog input	Ri = 100 kΩ, characteristic curve parameterizable, $f_{max} = 1k, 10 kHz, SELV$	◦ Ain1 0-10 V/PWM: analog input	D158 [2]		
	◦ Ain1 0-10 V/PWM (with pull up): analog input	Ri = 100 kΩ, characteristic curve parameterizable, $f_{max} = 1k, 10 kHz, SELV$	◦ Ain1 0-10 V/PWM (with pull up): analog input	D158 [9]		
	◦ DIn1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5 VDC SELV	◦ DIn1 (active high): digital input	D159 [0]		
IO2	◦ Ain1 0-10 V/PWM: analog input	Ri = 100 kΩ, characteristic curve parameterizable, $f_{max} = 1k, 10 kHz, SELV$	◦ Ain1 0-10 V/PWM: analog input	D159 [2]		
	◦ Ain2 4-20 mA: analog input	Ri = 125 Ω, characteristic curve parameterizable, SELV	◦ Ain2 4-20 mA: analog input	D159 [3]		
	◦ Tach out (open collector)	Umax=50VDC, Imax=20 mA, SELV	◦ Tach out (open collector)	D159 [5]		
	◦ Diagnostics out (open collector)	Umax=50VDC, Imax=20 mA, SELV	◦ Diagnostics out (open collector)	D159 [6]		
	◦ Alarm out (open collector)	Umax=50VDC, Imax=20 mA, SELV	◦ Alarm out (open collector)	D159 [10]		
	◦ Test pulse output addressing (open collector)	Umax=50VDC, Imax=20 mA, SELV	◦ Test pulse output addressing (open collector)	D159 [11]		
IO3	◦ DCI-output (open collector)	Umax=50VDC, Imax=20 mA, SELV	◦ DCI-output (open collector)	D159 [12]		
	◦ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5 VDC SELV	◦ Din3 (active high): digital input	D15A [0]		
	◦ Din3 (active low): digital input	active: applied voltage < 1.5 VDC, SELV not active: pin open or applied voltage 3.5-50 VDC SELV	◦ Din3 (active low): digital input	D15A [1]		
	◦ PWMIn3: digital PWM input, idle level high	PWM=40 Hz - 10 kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50 VDC not active: applied voltage < 1.5 VDC, SELV	◦ PWMIn3: digital PWM input, idle level high	D15A [7]		
	◦ PWMIn3: digital PWM input, idle level low	PWM=40 Hz - 10 kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50 VDC not active: applied voltage < 1.5 VDC, SELV	◦ PWMIn3: digital PWM input, idle level low	D15A [8]		
	◦ Aout3 0-10 V: analog input	function parameterizable, max. 5mA, max output frequency 300 Hz, SELV 0-10 V max. 5 mA, max. output frequency 300 Hz, SELV	◦ Aout3 0-10 V: analog input	D15A [4]		
	◦ Tach out (pulses)	0-10 V max. 5 mA, max. output frequency 300 Hz, SELV	◦ Tach out (pulses)	D15A [5]		
	◦ Diagnostics out (pulses)	0-10 V max. 5 mA, max. output frequency 300 Hz, SELV	◦ Diagnostics out (pulses)	D15A [6]		
	◦ Alarm out (pulses)	0-10 V max. 5 mA, max. output frequency 300 Hz, SELV	◦ Alarm out (pulses)	D15A [10]		
	◦ Test pulse output addressing (pulses)	0-10 V max. 5 mA, max. output frequency 300 Hz, SELV	◦ Test pulse output addressing (pulses)	D15A [11]		
COM	◦ DCI output (pulses)	0-10 V max. 5 mA, max. output frequency 300 Hz, SELV	◦ DCI output (pulses)	D15A [12]		
	RS485 bus connection	MODEBUS RTU, parameter specification V7, SELV				
RSA	Relay	250 VAC / 2 A (AC1)				
NC	Voltage output	Voltage parameterizable 3...3.24 VDC SELV 15...50VDC		D16E [-]		
Yout	Alternatively: input auxiliary power supply for parameterization via RS485/MODEBUS RTU without line voltage					

configurable IO functions: normal / Inverse

Advanced (A1)

Functions and parameter description
MODEBUS V7.0

- configurable function
- (c) function to be activated via IO Mode




8300100204
VBF0800TXNS

EC centrifugal module

backward-curved, single-intake
with cube design

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-223564-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	LwA	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	dB	m ³ /h	Pa	cfm	in. wg
1	3~	400	50	1750	15705	25.49	92	104	104	107	50990	0	30015	0.00
2	3~	400	50	1750	21537	34.11	89	99	102	104	44310	900	26080	3.61
3	3~	400	50	1750	24500	38.50	86	94	99	100	34235	1700	20150	6.82
4	3~	400	50	1750	22875	35.96	86	93	99	100	21595	2400	12710	9.64
5	3~	400	50	1575	11529	19.40	90	100	102	104	45920	0	27030	0.00
6	3~	400	50	1575	15683	25.40	86	96	99	100	39845	735	23450	2.95
7	3~	400	50	1575	18311	29.21	83	91	96	97	30935	1403	18210	5.63
8	3~	400	50	1575	16718	26.89	83	90	96	97	19410	1945	11425	7.81
9	3~	400	50	1225	5619	11.28	81	92	94	96	34975	0	20585	0.00
10	3~	400	50	1225	7519	13.78	79	89	92	93	30565	432	17990	1.73
11	3~	400	50	1225	8728	15.46	76	84	89	91	23970	844	14110	3.39
12	3~	400	50	1225	8035	14.48	77	84	90	91	15100	1176	8890	4.72
13	3~	400	50	875	2236	5.90	72	82	85	86	24945	0	14685	0.00
14	3~	400	50	875	2898	7.08	70	79	83	84	21780	220	12820	0.88
15	3~	400	50	875	3349	7.91	68	76	81	82	17100	429	10065	1.72
16	3~	400	50	875	3071	7.39	68	76	81	82	10760	596	6335	2.39

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · P_{fs} = Pressure increase

