

8300100274
VWA0910CTTRS

EC axial panel fan - AxiEco

with inlet ring and guard grill

ebm-papst Mulfingen GmbH & Co. KGaA & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
info1@de.fansco.com
www.fansco.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300100274	
Motor	E15035-120	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Status		prelim.
Speed (rpm)	min ⁻¹	1320
Power consumption	W	4750
Current draw	A	7.4
Max. back pressure	Pa	700
Max. back pressure	in. wg	2.81
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · oe = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	55.3	37.7	09 Power consumption P_{ed}	kW	4.39
02 Measurement category		A		09 Air flow q_v	m ³ /h	18395
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	458
04 Efficiency grade N		57.6	40	10 Speed (rpm) n	min ⁻¹	1315
05 Variable speed drive		Yes		11 Specific ratio*		1.01

Data obtained at optimum efficiency level.

* Specific ratio = $1 + p_g / 100\,000\text{ Pa}$

LU-220183

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

EC axial panel fan - AxiEco

with inlet ring and guard grill

Technical description

Weight	66.06 kg
Size	910 mm
Motor size	150
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum, painted gray
Impeller material	PP plastic, ABS ring plastic
Inlet ring material	Sheet steel, galvanized and coated with black plastic (RAL 9005)
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Airflow direction	V
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H2
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.4 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection - Vibration sensor
Power Factor Correction (PFC)	Passive (through low-capacitance DC link)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Electronic motor protection
Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.

8300100274
VWA0910CTTRS

EC axial panel fan - AxiEco


with inlet ring and guard grill

Conformity with standards	EN 61800-5-1; CE
Approval	UL 1004-7 + 60730-1

EC axial panel fan - AxiEco

with inlet ring and guard grill

Product drawing




1	Airflow direction "V"
2	Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm
3	Cable diameter min. 5 mm, max. 14 mm, tightening torque 6 ± 0.9 Nm
	(The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted)
4	Tightening torque 3 ± 0.3 Nm
5	Attachment holes for FlowGrid 91000-2-2957 (not included in scope of delivery)

EC axial panel fan - AxiEco

with inlet ring and guard grill

Connection diagram



No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V/PWM, Ri=100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Actual speed Characteristic curve parametrizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

EC axial panel fan - AxiEco

with inlet ring and guard grill

Terminal/plug assignment

configurable option			configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	CON2		configurable IO mode		electrical specification		OUTPUT															
Din1 (active high): digital input		active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC			D158 [0]	(selected directly via IO mode)																				
Ain1 0-10V/PWM: analog input		RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV			D158 [2]	(selected directly via IO mode)																				
Tach out (open collector output)		Umax = 50VDC, Imax = 20mA, SELV			D158 [5]	(selected directly via IO mode)																				
Diagnostics out (open collector output)		Umax = 50VDC, Imax = 20mA, SELV			D158 [6]	(selected directly via IO mode)																				
Din2 (active high): digital input		active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC			D159 [0]	(selected directly via IO mode)																				
Ain2 0-10V/PWM: analog input		RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV			D159 [2]	(selected directly via IO mode)																				
Ain2 4-20mA: analog input		RI = 125R, characteristic curve parameterizable, SELV			D159 [3]	(selected directly via IO mode)																				
Din3 (active high): digital input		active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC			D15A [0]	(selected directly via IO mode)																				
Din3 (active low): digital input		active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC			D15A [1]	(selected directly via IO mode)																				
PWMIn3: digital input idle level high		PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV		D15A [7]	(selected directly via IO mode)																					
PWMIn3: digital input idle level low		40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV		D15A [8]	(selected directly via IO mode)																					
Aout3 0-10V: analog output		function parameterizable, max. 5mA max output frequency 300Hz, SELV		D15A [4]	(selected directly via IO mode)																					
Tacho out (pulses), analog output		0-10Vmax. 5mA max output frequency 300Hz, SELV		D15A [5]	(selected directly via IO mode)																					
Diagnostics out (pulses)		0-10Vmax. 5mA max output frequency 300Hz, SELV		D15A [6]	(selected directly via IO mode)																					
RSA	RS485 bus connection,		MODBUS RTU, specification V6.4, SELV			(selected directly via IO mode)																				
RSB						(selected directly via IO mode)																				
Vout	voltage output		voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV		D16E [...] D16C [...] D148 [...] D12E [...] D104 [...] D147 [...] D101 [...]	(selected directly via IO mode)																				
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage		15...50VDC			(selected directly via IO mode)																				

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4


8300100274

VWA0910CTTRS

EC axial panel fan - AxiEco

with inlet ring and guard grill

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-220183-1
Date: 2022-03-31

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	LwA	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	dB	m ³ /h	Pa	cfm	in. wg
1	3~	400	50	1320	2814	4.58	86	92	94	96	28595	0	16830	0.00
2	3~	400	50	1320	3811	6.03	80	87	89	91	23615	250	13900	1.00
3	3~	400	50	1320	4426	6.93	77	85	88	90	17620	480	10370	1.93
4	3~	400	50	1320	4750	7.40	83	90	95	97	9670	700	5690	2.81
5	3~	400	50	1150	1873	3.05	83	89	91	93	24970	0	14695	0.00
6	3~	400	50	1150	2533	4.01	77	84	86	88	20610	190	12130	0.76
7	3~	400	50	1150	2947	4.61	74	81	85	86	15385	367	9055	1.47
8	3~	400	50	1150	3151	4.91	80	87	92	93	8445	535	4970	2.15
9	3~	400	50	950	1056	1.72	78	84	86	88	20630	0	12140	0.00
10	3~	400	50	950	1428	2.26	72	79	81	83	17025	130	10020	0.52
11	3~	400	50	950	1661	2.60	69	77	80	81	12710	251	7480	1.01
12	3~	400	50	950	1776	2.77	75	82	87	88	6975	365	4105	1.47
13	3~	400	50	750	520	0.85	72	78	80	82	16285	0	9585	0.00
14	3~	400	50	750	703	1.11	66	73	75	77	13445	81	7910	0.33
15	3~	400	50	750	817	1.28	63	71	74	75	10035	156	5905	0.63
16	3~	400	50	750	874	1.36	69	76	81	82	5505	228	3240	0.92

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · P_{fs} = Pressure increase