

8300100461
VBS0280CSLDS

EC centrifugal fan - RadiPac

backward-curved, single-intake

ebm-papst Mulfingen GmbH & Co. KGaA & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300100461	
Motor	E06001-17	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1450
Power consumption	W	60
Current draw	A	0.5
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

8300100461
VBS0280CSLDS

EC centrifugal fan - RadiPac

backward-curved, single-intake

Technical description


Weight	1.66 kg
Size	280 mm
Motor size	60
Rotor surface	Thick-film passivated
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Number of blades	5
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	<ul style="list-style-type: none">- Output 10 VDC, max. 1.1 mA- Locked-rotor detection- Tach output- Speed control- Power limiter- Motor current limitation- Soft start- Control input 0-10 VDC / PWM- Control interface with SELV potential safely disconnected from the mains- Overvoltage detection- Thermal overload protection for electronics/motor- Line undervoltage detection
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Electronic motor protection
With cable	Variable
Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 60034-1; EN 60204-1; EN 60335-1; CE
Comment on CE	Ecodesign Directive 2009/125/EC + Fan Directive (EC) No. 327/2011 does not apply, as power consumption <125W.

8300100461
VBS0280CSLDS

EC centrifugal fan - RadiPac


backward-curved, single-intake

Product drawing



1	Accessory part: Inlet ring 8217104581 with pressure tap (k-factor: 98) (not included in scope of delivery)
2	Max. clearance for screw 5 mm
3	Supply line (PWR) PVC AWG20 3x splice
4	Control wire (CTRL) PVC AWG22 4x splice


Accessory part



Inlet ring 8217104581 with pressure tap (k-factor: 98)

- 1 Fastening holes for FlowGrid 20280-2-2957 (not included in scope of delivery) are provided and must be subsequently opened as required

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	PWR	L	black	Power supply, phase, see nameplate for voltage range
	PWR	N	blue	Power supply, neutral conductor, see nameplate for voltage range
	PWR	PE	green/yellow	Protective earth
	CTRL	GND	blue	Reference ground for control interface, SELV
	CTRL	IO1	yellow	Factory setting: Analog input 0-10 V/PWM, Ri=100 KΩ, fPWM=1 kHz..10 kHz, Function: Speed set value Characteristic curve parameterizable (see "Input curve 1"), SELV Function parameterizable at the factory (see Optional interface functions table)
	CTRL	IO2	white	Factory setting: Open collector output, Umax=50 VDC, Imax= 10 mA, function: Tach output 1 pulse/revolution, SELV Function parameterizable at factory (see table Optional interface functions)
	CTRL	Vout	red	Voltage output 10 VDC +/-3%, Imax=1.1 mA Not short-circuit-proof, power supply for external devices, SELV

Terminal/plug assignment


	configurable IO mode	electrical specification						
IO1	◦ Din1 (high active): digital input	active: parameterizable voltage x-30 VDC not active: pin open or parameterizable voltage <x VDC, SELV						
	◦ Ain1 0-10 V/PWM: analog input	RI = 100 kΩ, characteristic curve parameterizable, $f_{\text{PWM}} = 1\text{k}..10\text{ kHz}$, SELV						
IO2	◦ Tach out (open collector)	Umax=50 VDC, Imax=10 mA, SELV						
	◦ Diagnostics out (open collector)	Umax=50 VDC, Imax=10 mA, SELV						
	◦ Alarm out (open collector)	Umax=50 VDC, Imax=10 mA, SELV						
	◦ Open collector	Umax=50 VDC, Imax=10 mA, SELV						
Vout	Voltage output	Voltage 10 VDC, SELV						

	INPUT	OUTPUT
source: set value	◦	
switch: parameter set: #1 / #2	◦	
switch: direction of rotation: cw / ccw	◦	
switch: enable/disable input	◦	
configurable function	◦	
signal: tach out		◦
signal: diagnostics out		◦
signal: alarm out		◦
signal: run monitoring		◦
signal: status		◦
signal: configurable function		◦

Basic (B4)
Factory configuration option upon request

◦ Factory configuration option

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-220535-1
Date: 2022-03-29
Nozzle: 8217102502

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	1~	230	50	1560	49	0.43	57	65	1645	0	970	0.00
2	1~	230	50	1500	59	0.50	52	60	1370	60	805	0.24
3	1~	230	50	1450	60	0.50	47	55	950	120	560	0.48
4	1~	230	50	1505	58	0.50	47	56	495	170	290	0.68
5	1~	230	50	1285	29	0.27	53	61	1355	0	795	0.00
6	1~	230	50	1280	37	0.33	49	56	1160	43	680	0.17
7	1~	230	50	1285	41	0.36	44	52	835	93	495	0.37
8	1~	230	50	1285	36	0.32	43	51	420	123	250	0.49
9	1~	230	50	1125	20	0.19	50	59	1185	0	695	0.00
10	1~	230	50	1125	25	0.23	46	54	1020	33	600	0.13
11	1~	230	50	1125	28	0.26	41	49	735	71	430	0.29
12	1~	230	50	1125	24	0.23	39	47	370	95	215	0.38
13	1~	230	50	810	9.5	0.10	42	50	840	0	495	0.00
14	1~	230	50	810	11	0.11	39	47	725	17	425	0.07
15	1~	230	50	810	12	0.12	35	43	525	36	310	0.14
16	1~	230	50	810	11	0.11	31	39	265	49	155	0.20

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · P_{fs} = Pressure increase