

8300100534
VBS0500CTTLS

EC centrifugal fan - RadiPac

backward-curved, single-intake

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.fansco.com
www.fansco.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344
General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300100534	
Motor	E15037-55	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Status		prelim.
Speed (rpm)	min ⁻¹	2450
Power consumption	W	4000
Current draw	A	5.8
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	71.9	57.8	09 Power consumption P_{ed}	kW	4
02 Measurement category		A		09 Air flow q_v	m³/h	10385
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	959
04 Efficiency grade N		76.1	62	10 Speed (rpm) n	min ⁻¹	2435
05 Variable speed drive		Yes		11 Specific ratio*		1.01

Data obtained at optimum efficiency level.
The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$ LU-220201

Technical description

Weight	23.44 kg
Size	500 mm
Motor size	150
Rotor surface	Painted black
Terminal box material	Die-cast aluminum
Impeller material	PP plastic
Number of blades	5
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing; (sealed)
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.4 - Motor current limitation - PFC, active - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection - Vibration sensor
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-4 (industrial environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Electronic motor protection
Protection class assignment	I; If a protective earth is connected to the PE connection point. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.


8300100534
VBS0500CTTLS

EC centrifugal fan - RadiPac

backward-curved, single-intake


Conformity with standards	EN 61800-5-1; UKCA; CE
Approval	UL 1004-7 + 60730-1; CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC

Product drawing



1	Accessory part: Inlet ring 8217102238 with pressure tap (k-factor: 290) (not included in scope of delivery)
2	Max. clearance for screw 20 mm
3	Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm
4	Cable diameter min. 5 mm, max. 14 mm, tightening torque 6 ± 0.9 Nm
	(The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted)
5	Tightening torque 3 ± 0.3 Nm

Accessory part




- | | |
|---|--|
| 1 | Fastening holes for FlowGrid 35505-2-2957 (not included in scope of delivery) are provided and must be subsequently opened as required |
| | Inlet ring 8217102238 with pressure tap (k-factor: 290) |

EC centrifugal fan - RadiPac

backward-curved, single-intake

Connection diagram



No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V/PWM, Ri=100 kΩ, function: set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Actual speed Characteristic curve parametrizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC +/-5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

Terminal/plug assignment

○ configurable option			configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification												
CON2	configurable IO mode	○ Din1 (active high): digital input			active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		○ Ain1 0-10V/PWM: analog input			RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
		○ Tach out (open collector output)			Umax = 50VDC, Imax = 20mA, SELV												
		○ Diagnostics out (open collector output)			Umax = 50VDC, Imax = 20mA, SELV												
IO1	configurable IO mode	○ Din2 (active high): digital input			active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		○ Ain2 0-10V/PWM: analog input			RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
		○ Ain2 4-20mA: analog input			RI = 125R, characteristic curve parameterizable, SELV												
		○ Din3 (active high): digital input			active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
IO2	configurable IO mode	○ Din3 (active low): digital input			active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
		○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV														
		○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV														
		○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV														
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2	configurable IO mode	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV																
○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV																
○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV																
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2	configurable IO mode	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV																
○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV																
○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV																
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2	configurable IO mode	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV																
○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV																
○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV																
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2	configurable IO mode	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV																
○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV																
○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV																
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2	configurable IO mode	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV																
○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV																
○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV																
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2	configurable IO mode	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV																
○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV																
○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV																
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2	configurable IO mode	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV																
○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV																
○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV																
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2	configurable IO mode	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV																
○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV																
○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV																
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4


configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2	configurable IO mode	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC												
○ PWMIn3: digital input idle level high	PWM = 40Hz - 10kHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV																
○ PWMIn3: digital input idle level low	40Hz - 10kHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV																
○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV																
IO3	configurable IO mode	○ Tacho out (pulses), analog output	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ Diagnostics out (pulses)	0-10Vmax. 5mA max output frequency 300Hz, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
		○ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV															
	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15..50VDC															

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification															
		CON2	configurable IO mode	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
				○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV												
		IO1	configurable IO mode	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
				○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, $f_{PWM} = 1k..10kHz$, SELV												
				○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV												
				○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC												
		IO2															

◦ configurable option
For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-220201-1
Date: 2022-04-28
Nozzle: 8217101923

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	LwA	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	dB	m³/h	Pa	cfm	in. wg
1	3~	400	50	2450	2647	3.82	85	93	97	98	15000	0	8830	0.00
2	3~	400	50	2450	3651	5.27	79	87	92	93	12760	600	7510	2.41
3	3~	400	50	2450	4000	5.80	73	81	87	88	9030	1100	5315	4.42
4	3~	400	50	2450	3715	5.36	79	86	92	93	5280	1400	3110	5.62
5	3~	400	50	2150	1780	2.57	82	90	93	95	13140	0	7735	0.00
6	3~	400	50	2150	2454	3.54	76	84	88	90	11180	457	6580	1.83
7	3~	400	50	2150	2790	4.03	70	78	84	85	7995	866	4705	3.48
8	3~	400	50	2150	2516	3.63	76	83	89	90	4635	1079	2730	4.33
9	3~	400	50	1850	1134	1.64	78	86	90	91	11305	0	6655	0.00
10	3~	400	50	1850	1563	2.26	72	80	84	86	9620	339	5660	1.36
11	3~	400	50	1850	1778	2.57	66	74	81	81	6875	641	4050	2.57
12	3~	400	50	1850	1603	2.31	72	79	85	86	3990	799	2350	3.21
13	3~	400	50	1550	667	0.96	73	82	85	87	9475	0	5575	0.00
14	3~	400	50	1550	919	1.33	67	75	80	81	8060	238	4745	0.96
15	3~	400	50	1550	1046	1.51	62	70	76	77	5760	450	3390	1.81
16	3~	400	50	1550	943	1.36	68	75	81	82	3345	561	1970	2.25

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · P_{fs} = Pressure increase