

8300100656
VBH0190SSLBS

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300100656	
Motor	E06001-10	

Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	3400
Power consumption	W	85
Current draw	A	0.7
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

8300100656
VBH0190SSLBS

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

Technical description


Weight	1.34 kg
Size	190 mm
Motor size	60
Rotor surface	Thick-film passivated
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Housing material	PP plastic
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Locked-rotor detection - Tach output - Speed control - Power limiter - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Electronic motor protection
With cable	Variable
Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 60034-1; EN 60204-1; EN 60335-1; CE; UKCA
Comment on CE	Ecodesign Directive 2009/125/EC + Fan Directive (EC) No. 327/2011 does not apply, as power consumption <125W.
Approval	CSA C22.2 No. 77 + CAN/CSA-E60730-1; UL 1004-7 + 60730-1

8300100656
VBH0190SSLBS

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

Product drawing




1	Supply line (PWR) PVC AWG20 3x splice
2	Control wire (CTRL) PVC AWG22 4x splice
3	Fastening holes for FlowGrid 8217117433 (not included in scope of delivery) are provided and must only be used for FlowGrid

EC centrifugal module - RadiCal


backward-curved, single-intake
with housing

Mounting dimensions



- | | |
|---|---|
| 1 | Installation of motor plate |
| 2 | Installation of nozzle plate on outlet side |
| 3 | Installation of nozzle plate on intake side |

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	PWR	L	black	Power supply, phase, see nameplate for voltage range
	PWR	N	blue	Power supply, neutral conductor, see nameplate for voltage range
	PWR	PE	green/yellow	Protective earth
	CTRL	GND	blue	Reference ground for control interface, SELV
	CTRL	IO1	yellow	Factory setting: Analog input 0-10 V/PWM, Ri=100 KΩ, fPWM=1 kHz..10 kHz, Function: Speed set value Characteristic curve parameterizable (see "Input curve 1"), SELV Function parameterizable at the factory (see Optional interface functions table)
	CTRL	IO2	white	Factory setting: Open collector output, Umax=50 VDC, Imax= 10 mA, function: Tach output 1 pulse/revolution, SELV Function parameterizable at factory (see table Optional interface functions)
	CTRL	Vout	red	Voltage output 10 VDC +/-3%, Imax=1.1 mA Not short-circuit-proof, power supply for external devices, SELV

8300100656
VBH0190SSLBS

EC centrifugal module - RadiCal

backward-curved, single-intake

with housing

Terminal/plug assignment


		electrical specification		configurable IO mode		INPUT		OUTPUT			
IO1	Din1 (high active): digital input	active: parameterizable voltage x-30 VDC not active: pin open or parameterizable voltage <x VDC, SELV Ri = 100 kΩ, characteristic curve parameterizable, f _{PWM} = 1k..10 kHz, SELV		Ain1 0-10 V/PWM: analog input		source: set value					
						switch: parameter set: #1 / #2					
						switch: direction of rotation: cw / ccw					
						switch: enable/disable input					
						configurable function					
IO2	Tach out (open collector) Diagnostics out (open collector) Alarm out (open collector) Open collector	Umax=50 VDC, Imax=10 mA, SELV Umax=50 VDC, Imax=10 mA, SELV Umax=50 VDC, Imax=10 mA, SELV Umax=50 VDC, Imax=10 mA, SELV				signal: tach out					
						signal: diagnostics out					
						signal: alarm out					
						signal: run monitoring					
Vout	Voltage output	Voltage 10 VDC, SELV				signal: status					
						signal: configurable function					

Basic (B4)

Factory configuration option upon request

Factory configuration option

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-221735-1
Date: 2022-07-01
Nozzle: 8217116915

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	in. wg
1	1~	230	50	3675	63	0.53	65	73	880	0	520	0.00
2	1~	230	50	3600	85	0.70	61	69	725	190	425	0.76
3	1~	230	50	3400	85	0.70	60	68	515	330	300	1.32
4	1~	230	50	3510	85	0.70	67	75	285	450	170	1.81
5	1~	230	50	3000	34	0.29	60	68	720	0	425	0.00
6	1~	230	50	3000	50	0.40	57	64	605	133	355	0.53
7	1~	230	50	3000	61	0.50	56	64	455	260	265	1.04
8	1~	230	50	3000	54	0.44	62	71	245	330	145	1.32
9	1~	230	50	2500	20	0.17	55	63	600	0	355	0.00
10	1~	230	50	2500	29	0.23	52	60	505	93	295	0.37
11	1~	230	50	2500	35	0.29	51	60	380	181	220	0.73
12	1~	230	50	2500	32	0.26	58	66	205	229	120	0.92
13	1~	230	50	2000	10	0.09	50	57	480	0	280	0.00
14	1~	230	50	2000	15	0.12	46	54	405	59	240	0.24
15	1~	230	50	2000	18	0.15	46	54	305	116	180	0.47
16	1~	230	50	2000	16	0.13	52	61	165	147	95	0.59

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{fs} = Pressure increase