

8300101210
VUB0450CSNJS

EC axial panel fan - AxiEco

with inlet ring and air inlet grille

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

| | | |
|--------------------------|-------------------|------------|
| Item | 8300101210 | |
| Motor | E07433-43 | |
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Nominal voltage range | VAC | 200 .. 240 |
| Frequency | Hz | 50/60 |
| Method of obtaining data | | ml |
| Status | | prelim. |
| Speed (rpm) | min ⁻¹ | 960 |
| Power consumption | W | 170 |
| Current draw | A | 1.4 |
| Max. back pressure | Pa | 105 |
| Max. back pressure | in. wg | 0.42 |
| Min. ambient temperature | °C | -25 |
| Max. ambient temperature | °C | 60 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

| | | Actual | Req. 2015 | | | |
|-----------------------------------|---|--------|-----------|-------------------------------|-------------------|------|
| 01 Overall efficiency η_{es} | % | 48.7 | 28.8 | 09 Power consumption P_{ed} | kW | 0.16 |
| 02 Measurement category | | A | | 09 Air flow q_v | m ³ /h | 3210 |
| 03 Efficiency category | | Static | | 09 Pressure increase p_{fs} | Pa | 82 |
| 04 Efficiency grade N | | 59.9 | 40 | 10 Speed (rpm) n | min ⁻¹ | 980 |
| 05 Variable speed drive | | Yes | | 11 Specific ratio* | | 1.00 |

Data obtained at optimum efficiency level.

* Specific ratio = $1 + p_s / 100\,000\text{ Pa}$

LU-230360

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

8300101210
VUB0450CSNJS

EC axial panel fan - AxiEco

with inlet ring and air inlet grille

Technical description


| | |
|--|--|
| Weight | 5,4 |
| Size | 450 mm |
| Motor size | 74 |
| Rotor surface | Thick-film passivated |
| Impeller material | PP plastic |
| Inlet ring material | ABS plastic |
| Flowgrid material | PP plastic |
| Number of blades | 5 |
| Airflow direction | A |
| Direction of rotation | Counterclockwise, viewed toward rotor |
| Degree of protection | IP54 |
| Insulation class | "B" |
| Moisture (F) / Environmental (H) protection class | H1 |
| Max. permitted ambient temp. for motor (transport/storage) | +80 °C |
| Min. permitted ambient temp. for motor (transport/storage) | -40 °C |
| Installation position | Any |
| Condensation drainage holes | None, open rotor |
| Mode | S1 |
| Motor bearing | Ball bearing |
| Technical features | <ul style="list-style-type: none">- Output 10 VDC, max. 10 mA- Locked-rotor detection- Tach output- Speed control- Power limiter- Motor current limitation- Soft start- Control input 0-10 VDC / PWM- Control interface with SELV potential safely disconnected from the mains- Overvoltage detection- Thermal overload protection for electronics/motor- Line undervoltage detection |
| EMC immunity to interference | According to EN 61000-6-2 (industrial environment) |
| EMC interference emission | According to EN 61000-6-4 (industrial environment) |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | <= 3.5 mA |
| Motor protection | Electronic motor protection |
| With cable | Variable |
| Protection class assignment | I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation. |
| Conformity with standards | EN 60335-1; EN 60034-1; EN 60204-1; CE; UKCA |
| Approval | CSA C22.2 No. 77 + CAN/CSA-E60730-1; UL 1004-7 + 60730-1 |

8300101210
VUB0450CSNJS

EC axial panel fan - AxiEco

with inlet ring and air inlet grille

Product drawing




| | |
|---|---|
| 1 | Direction of air flow "A" |
| 2 | Supply line (PWR) PVC AWG20 |
| | 3x splice |
| 3 | Control wire (CTRL) PVC AWG22 |
| | 6x splice |
| 4 | Fastening holes are provided and must be opened subsequently if necessary |

8300101210
VUB0450CSNJS

EC axial panel fan - AxiEco

with inlet ring and air inlet grille

Connection diagram



| No. | Conn. | Designation | Color | Function/assignment |
|-----|-------|-------------|--------------|--|
| | PWR | L | black | Power supply, phase, see nameplate for voltage range |
| | PWR | N | blue | Power supply, neutral conductor, see nameplate for voltage range |
| | PWR | PE | green/yellow | Protective earth |
| | | | | |
| | CTRL | GND | blue | Reference ground for control interface, SELV |
| | CTRL | IO1 | yellow | Factory setting: Analog input 0-10 V/PWM, Ri=100 KΩ, fPWM=1 kHz..10 kHz, Function: Speed set value Characteristic curve parameterizable (see "Input curve 1"), SELV Function parameterizable at the factory (see Optional interface functions table) |
| | CTRL | IO2 | white | Factory setting: Open collector output, Umax=50 VDC, I _{max} = 10 mA, function: Tach output 1 pulse/revolution, SELV Function parameterizable at factory (see table Optional interface functions) |
| | CTRL | Vout | red | Voltage output 10 VDC +/-3%, I _{max} =10 mA Short-circuit-proof, power supply for external devices, SELV |
| | CTRL | - | gray | No function |
| | CTRL | - | brown | No function |

EC axial panel fan - AxiEco

with inlet ring and air inlet grille

Terminal/plug assignment

| | configurable IO mode | electrical specification | | | | | | |
|------|-----------------------------------|--|--|--|--|--|--|--|
| IO1 | Din1 (high active): digital input | active: parameterizable voltage x-30 VDC not active: pin open or parameterizable voltage <x VDC, SELV | | | | | | |
| | Ain1 0-10 V/PWM: analog input | RI = 100 kΩ, characteristic curve parameterizable, $f_{\text{PWM}} = 1\text{ k}..10\text{ kHz}$, SELV | | | | | | |
| | Tach out (open collector) | Umax=50 VDC, Imax=10 mA, SELV | | | | | | |
| | Diagnosics out (open collector) | Umax=50 VDC, Imax=10 mA, SELV | | | | | | |
| IO2 | Alarm out (open collector) | Umax=50 VDC, Imax=10 mA, SELV | | | | | | |
| | Open collector | Umax=50 VDC, Imax=10 mA, SELV | | | | | | |
| Vout | Voltage output | Voltage 10 VDC, SELV | | | | | | |

| | INPUT | OUTPUT | | | | | | |
|---|-------|--------|--|--|--|--|--|--|
| source: set value | | | | | | | | |
| switch: parameter set: #1 / #2 | | | | | | | | |
| switch: direction of rotation: cw / ccw | | | | | | | | |
| switch: enable/disable input | | | | | | | | |
| configurable function | | | | | | | | |
| signal: tach out | | | | | | | | |
| signal: diagnostics out | | | | | | | | |
| signal: alarm out | | | | | | | | |
| signal: run monitoring | | | | | | | | |
| signal: status | | | | | | | | |
| signal: configurable function | | | | | | | | |


Basic (B4)
Factory configuration option upon request

o Factory configuration option

EC axial panel fan - AxiEco

with inlet ring and air inlet grille

Curves: Air performance 50 Hz



$\rho = 1.178 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-230360-1
Date: 2024-01-16
Nozzle: 8217118762

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

| | Wired | U | f | n | P _e | I | LpA _{in} | LwA _{in} | LwA _{out} | LwA | q _v | P _{fs} | q _v | P _{fs} |
|----|-------|-----|----|-------------------|----------------|------|-------------------|-------------------|--------------------|-----|-------------------|-----------------|----------------|-----------------|
| | | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | dB(A) | dB | m ³ /h | Pa | cfm | in. wg |
| 1 | 1~ | 230 | 50 | 1025 | 133 | 1.14 | 63 | 70 | 73 | 75 | 4960 | 0 | 2920 | 0.00 |
| 2 | 1~ | 230 | 50 | 1025 | 164 | 1.38 | 60 | 68 | 71 | 73 | 4370 | 40 | 2575 | 0.16 |
| 3 | 1~ | 230 | 50 | 985 | 170 | 1.40 | 56 | 64 | 67 | 69 | 3410 | 75 | 2010 | 0.30 |
| 4 | 1~ | 230 | 50 | 960 | 170 | 1.40 | 57 | 64 | 67 | 69 | 1955 | 105 | 1150 | 0.42 |
| 5 | 1~ | 230 | 50 | 900 | 90 | 0.77 | 59 | 67 | 70 | 72 | 4350 | 0 | 2560 | 0.00 |
| 6 | 1~ | 230 | 50 | 900 | 111 | 0.93 | 57 | 65 | 68 | 69 | 3835 | 31 | 2260 | 0.12 |
| 7 | 1~ | 230 | 50 | 900 | 129 | 1.08 | 54 | 62 | 65 | 66 | 3115 | 63 | 1835 | 0.25 |
| 8 | 1~ | 230 | 50 | 900 | 138 | 1.17 | 55 | 63 | 66 | 67 | 1830 | 92 | 1075 | 0.37 |
| 9 | 1~ | 230 | 50 | 750 | 52 | 0.44 | 55 | 62 | 65 | 67 | 3625 | 0 | 2135 | 0.00 |
| 10 | 1~ | 230 | 50 | 750 | 64 | 0.54 | 52 | 60 | 63 | 65 | 3195 | 22 | 1880 | 0.09 |
| 11 | 1~ | 230 | 50 | 750 | 75 | 0.63 | 49 | 57 | 60 | 62 | 2600 | 44 | 1530 | 0.18 |
| 12 | 1~ | 230 | 50 | 750 | 80 | 0.67 | 51 | 58 | 61 | 63 | 1525 | 64 | 895 | 0.26 |
| 13 | 1~ | 230 | 50 | 600 | 27 | 0.23 | 49 | 57 | 60 | 61 | 2900 | 0 | 1705 | 0.00 |
| 14 | 1~ | 230 | 50 | 600 | 33 | 0.28 | 47 | 55 | 57 | 59 | 2560 | 14 | 1505 | 0.06 |
| 15 | 1~ | 230 | 50 | 600 | 38 | 0.32 | 44 | 51 | 54 | 56 | 2080 | 28 | 1225 | 0.11 |
| 16 | 1~ | 230 | 50 | 600 | 41 | 0.35 | 45 | 53 | 55 | 57 | 1220 | 41 | 715 | 0.16 |

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · P_{fs} = Pressure increase