

8300101417
VBH0206SSLES

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300101417	
Motor	E06002-23	

Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	3250
Power consumption	W	120
Current draw	A	1.0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

8300101417
VBH0206SSLES

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

Technical description


Size	206 mm
Motor size	60
Rotor surface	Thick-film passivated
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Housing material	PP plastic
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Locked-rotor detection - Tach output - Speed control - Power limiter - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Electronic motor protection
With cable	Variable
Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 60335-1; EN 60034-1; EN 60204-1; UKCA; CE
Comment on CE	Ecodesign Directive 2009/125/EC + Fan Directive (EC) No. 327/2011 does not apply, as power consumption <125W.

8300101417
VBH0206SSLES

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

Product drawing




1	Supply line (PWR) PVC AWG20 3x splice
2	Control wire (CTRL) PVC AWG22 4x splice
3	Fastening holes for FlowGrid 8217118542 (not included in scope of delivery) are provided and must only be used for FlowGrid

EC centrifugal module - RadiCal


backward-curved, single-intake
with housing

Mounting dimensions



- | | |
|---|---|
| 1 | Installation of motor plate |
| 2 | Installation of nozzle plate on outlet side |
| 3 | Installation of nozzle plate on intake side |

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
	PWR	L	black	Power supply, phase, see nameplate for voltage range
	PWR	N	blue	Power supply, neutral conductor, see nameplate for voltage range
	PWR	PE	green/yellow	Protective earth
	CTRL	GND	blue	Reference ground for control interface, SELV
	CTRL	IO1	yellow	Factory setting: Analog input 0-10 V/PWM, Ri=100 KΩ, fPWM=1 kHz..10 kHz, Function: Speed set value Characteristic curve parameterizable (see "Input curve 1"), SELV Function parameterizable at the factory (see Optional interface functions table)
	CTRL	IO2	white	Factory setting: Open collector output, Umax=50 VDC, Imax= 10 mA, function: Tach output 1 pulse/revolution, SELV Function parameterizable at factory (see table Optional interface functions)
	CTRL	Vout	red	Voltage output 10 VDC +/-3%, Imax=10 mA Short-circuit-proof, power supply for external devices, SELV

VBH0206SSLES

backward-curved, single-intake
with housing

Basic (B4)									
Factory configuration option upon request									
Factory configuration option									
IO1	configurable IO mode			electrical specification			INPUT		
							OUTPUT		
IO2	Dim1 (high active): digital input			active: parameterizable voltage x-30 VDC					
				not active: pin open or parameterizable voltage <x VDC, SELV					
	Ain1 0-10 V/PWM: analog input			Ri = 100 kΩ, characteristic curve parameterizable, $f_{PWM} = 1k..10\text{ kHz}$, SELV					
	Tach out (open collector)			Umax=50 VDC, Imax=10 mA, SELV					
	Diagnostics out (open collector)			Umax=50 VDC, Imax=10 mA, SELV					
Vout	Alarm out (open collector)			Umax=50 VDC, Imax=10 mA, SELV					
	Open collector			Umax=50 VDC, Imax=10 mA, SELV					
	Voltage output			Voltage 10 VDC, SELV					

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-226178-1
Date: 2023-07-27
Nozzle: 8217118633

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	in. wg
1	1~	230	50	3555	89	0.76	68	75	1145	0	675	0.00
2	1~	230	50	3445	114	0.96	63	71	930	220	550	0.88
3	1~	230	50	3250	120	1.00	61	69	610	400	360	1.61
4	1~	230	50	3310	120	1.00	65	73	445	480	265	1.93
5	1~	230	50	3100	59	0.50	64	72	995	0	585	0.00
6	1~	230	50	3100	83	0.70	61	68	835	179	495	0.72
7	1~	230	50	3100	102	0.85	59	67	580	360	340	1.45
8	1~	230	50	3100	99	0.83	63	72	420	422	245	1.69
9	1~	230	50	2600	35	0.30	60	67	835	0	490	0.00
10	1~	230	50	2600	49	0.41	56	64	700	126	415	0.51
11	1~	230	50	2600	60	0.50	55	63	485	253	285	1.02
12	1~	230	50	2600	58	0.49	59	67	350	297	205	1.19
13	1~	230	50	2100	18	0.16	55	62	675	0	395	0.00
14	1~	230	50	2100	26	0.22	51	58	565	82	335	0.33
15	1~	230	50	2100	32	0.27	50	58	390	165	230	0.66
16	1~	230	50	2100	31	0.26	53	62	285	194	165	0.78

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{fs} = Pressure increase