



8412 N/2GH-214

8412N/2GH-214 (9292506214) ebmpapst Datasheet FansCo
sales@fansco.com
www.fansco.com

Customer specification: No
Version: 1.0
Created: 28.06.2011

INDEX

1	General	2
2	Mechanics	2
2.1	General.....	2
2.2	Motor	2
2.3	Connections	3
3	Operating Data.....	4
3.1	Operating Data - Electrical Interface - Input.....	4
3.2	Electrical Operating Data	4
3.3	Operating Data - Electrical Interface -Output	4
3.4	Electrical Features.....	5
3.5	Aerodynamic	6
3.6	Sound Data	6
4	Environment.....	6
4.1	General.....	6
4.2	Climatic requirements.....	7
4.3	Mechanical requirements	8
4.4	EMC.....	8
5	Safety.....	8
5.1	Electrical Safety.....	8
5.2	Approval Tests	8
6	Reliability.....	8
6.1	General.....	8
6.2	Additional Data	8

Special features according to QMH 2-5.4.7 and company standard 1-23.00 have the following definitions:

"A" : Product features or process parameters which influence the safety of a product or the compliance of legal requirements. (Must not necessary verified and documented 100%. Standards and legal requirements must be considered.)

"FK" : Product features or process parameters which influence the fit and function of a product or which have to be controlled or documented for some other reasons (e.g. Customer requirements).



1 General

Fan type	Fan	
Rotational direction looking at rotor	counterclockwise	FK
Airflow direction	Air outlet over struts	FK
Bearing system	Sleeve bearing	
Lubrication	see sectional drawing of the bearing	
Mounting position	any	
Tolerance		
Balancing grade	16,0	FK
Impeller weight	30,3 g	

2 Mechanics

2.1 General

Width	80,0 mm	
Height	80,0 mm	
Depth	25,4 mm	
Diameter	0,0 mm	
Weight	0,095 kg	
Housing material	Plastic	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges	wire outlet corner: 50 Ncm remaining corners: 70 Ncm	
Screw size	ISO 4762 - M4 degreased, without an additional brace and without washer	


2.2 Motor

Type of motor	Electronically commutated external rotor	
Diameter of the motor	25,0 mm	
Height of the motor	6,0 mm	
Number of phases	1	
Number of windings	1	
Operating mode	Continuous duty	
Insulation material class	E	



2.3 Connections

Electrical connection	Wires - Plug	
Length of lead wire	323 mm	
Tolerance		+/- 10,0 mm
Length of tube		
Tolerance		
Wire gauge (AWG)	24	
Insulation diameter	1,55 mm	
Plug	see drawing	
Contact	see drawing	



	Colour	Operation
Wire 1	red	+ UB
Wire 2	blue	- GND
Wire 3	white	Tacho

The auxiliaries shown on the schematic diagram (which are required for the intended use) are not part of our delivery.



3 Operating Data

3.1 Operating Data - Electrical Interface - Input

Control input	None
---------------	------

3.2 Electrical Operating Data

Measurement conditions: Normal air density = 1,2 kg/m³; Temperature 23°C +/- 3°C; Motor axis horizontal; warm-up time before measuring 5 minutes (unless otherwise specified). In the intake and outlet area should not be any solid obstruction within 0,5 m.

$\Delta p = 0$: corresp. to free air flow (see section 3.5)

I: corresp. to arithm. mean current value


Features	Condition	Symbol	Values		
Voltage range	$\Delta p = 0$	U	8,0 V		13,2 V
Nominal voltage	$\Delta p = 0$	U_N		12,0 V	
Power consumption	$\Delta p = 0$	P	1,1 W	2,8 W	3,4 W
Tolerance	0001		+/- 17,5 %	+/- 12,5 %	+/- 15,0 %
Current consumption	$\Delta p = 0$	I	140 mA	240 mA*)	260 mA
Tolerance	0001		+/- 17,5 %	+/- 12,5 %	+/- 15,0 %
Speed	$\Delta p = 0$	n	2.350 1/min	3.600 1/min*)	3.900 1/min
Tolerance	0001		+/- 12,5 %	+/- 7,5 %	+/- 10,0 %
Starting current consumption				910 mA	

*) Attention: Marked values are "FK" features

3.3 Operating Data - Electrical Interface -Output

Tacho type	/2 (Open collector)
------------	---------------------

Signal-Ausgangsspannung / Signal output voltage



$$R_a = \frac{U_{BS} - U_{S \text{ Low}}}{I_{\text{Sink}}}$$


Features	Note	Values
Tacho operating voltage (UBS)		<= 28 V
Tacho signal Low *)	I sink: 2 mA	<= 0,4 V
Tacho signal High *)	I source: 0 mA	<= 28 V
Maximum sink current		<= 4 mA
External resistor	External resistor Ra from UBS to US required. All voltages measured to GND.	
Tacho frequency *)	(2 x n) / 60	
Tacho isolated from motor	No	
Slew rate		=> 0,5 V/us

*) Attention: Marked values are "FK" features

Alarm type	None
------------	------

3.4 Electrical Features

Electronic function	None	
Reversed polarity protection	Rectifying diode	A
Max. residual current at Un	IF <= 5 uA	
Locked rotor protection	Auto restart	A
Locked rotor current at Un	approx. 910 mA	
Clock signal t3/t4 at locked rotor	Typical: 0,2 s / 1,1 s t3: 0,06 s... 0,77 s t4: 0,3 s... 3,6 s	



3.5 Aerodynamic

Measurement conditions: Measured with a double chamber intake rig acc. to DIN EN ISO 5801.
Normal air density = 1,2 kg/m³; Temperature 23°C +/- 3°C;
In the intake and outlet area should not be any solid obstruction within 0,5 m.

a.) Operation condition:

3.600 1/min at free air flow		
Max. free-air flow ($\Delta p = 0 / \dot{V} = \text{max.}$)	78,0 m ³ /h	FK
Max. static pressure ($\Delta p = \text{max.} / \dot{V} = 0$)	53 Pa	FK

3.6 Sound Data

Measurement conditions: Sound pressure level: 1 Meter distance between microphone and the air intake.
Sound power level: Acc. to DIN 45635 part 38 (ISO 10302)
Measured in a semianchoic chamber with a background noise level of L_p(A) < 5 dB(A)
For further measurement conditions see section 3.5

a.) Operation condition:

3.600 1/min at free air flow		
Optimal operating point	64,0 m ³ /h @ 14,0 Pa	
Sound power level at the optimal operating point	5,0 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	37,0 dB(A)	

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
--	--------	--



Max. permitted ambient temperature TU max.	70 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic requirements*)

Humidity requirements	humid heat, constant; according to DIN EN 60068-2-78, 14 days	
Water exposure	None	
Radiation exposure	None	
Dust requirements	None	
Salt fog requirements	None	
Harmful gas requirements	None	

*) Permitted application area:

The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoided.

Pollution degree 1 (according DIN EN 60664-1)

There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.



4.3 Mechanical requirements

Please require severity levels and specification parameters from the responsible development departments

4.4 EMC

not specified

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	Not applicable Not applicable	A
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Air and leakage distances	1,0 mm / 1,2 mm	
Protection class	III	

5.2 Approval Tests

CE	Yes
UL	Yes
VDE	Yes
CSA	Yes
CCC	No

The approval tests are observed to:
U approval max.:13,2 V @ TU approval max.: 70,0 °C

6 Reliability

6.1 General

Life expectancy L10 at TU = 40 °C	70.000 h	
Life expectancy L10 at TU max.	35.000 h	

6.2 Additional Data



not specified