

EC axial fan

sickled blades (S series)

**ebm-papst Mulfingen GmbH & Co. KG**

Bachmühle 2

D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

sales@fansco.com

www.fansco.com

Nominal data

Type	A1G200-AI77-52	
Motor	M1G074-BF	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Frequency	Hz	-
Type of data definition		rfa
Speed	min ⁻¹	2950
Power input	W	55
Current draw	A	2.6
Max. back pressure	Pa	120
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations


EC axial fan

sickled blades (S series)

Technical features

Size	200 mm
Operation mode	Continuous operation (S1)
Direction of rotation	"A"
Mounting position	Any
Humidity class	F0
Insulation class	"B"
Cable exit	Variable
Motor bearing	Ball bearing
Mass	1.5 kg
Material of electronics housing	Rotor: Coated in black
Material of impeller	Sheet steel, coated in black
Motor protection	Reverse polarity and locked-rotor protection
Number of blades	9
Type of protection	IP 42
Protection class	I
Technical features	Control input 0-10 VDC / PWM, tach output, polarity and locked rotor protection
Approval	CSA C22.2 Nr.77; UL 1004-1



Product drawing



EC axial fan


sickled blades (S series)

Connection screen



Line	Signal	Colour	Assignment / function	Line	Signal	Colour	Assignment / function
1	+	red	maximum ripple ± 3.5 %	1	Tacho	white	Tach output: pulses per revolution
	GND	blue	GND		0-10 V / PWM	yellow	Control input

Charts: Air flow



Measured values

	n	P _e
	min ⁻¹	W
1'	2300	73
2'	2970	77
3'	3100	80
4'	2970	80
1	2950	55
2	2890	58
3	2800	61
4	2780	63
5	2270	27
6	2230	28
7	2170	29
8	2130	30