

# AC axial fan

straight blades (A series)



A2E200-AF02-51 ebmpapst Datasheet  
sales@fansco.com  
www.fansco.com

## Nominal data

|                             |                   |      |      |
|-----------------------------|-------------------|------|------|
| Type                        | A2E200-AF02-51    |      |      |
| Motor                       | M2E068-CA         |      |      |
| Phase                       |                   | 1~   | 1~   |
| Nominal voltage             | VAC               | 230  | 230  |
| Frequency                   | Hz                | 50   | 60   |
| Method of obtaining data    |                   | fa   | fa   |
| Valid for approval/standard |                   | CE   | CE   |
| Speed                       | min <sup>-1</sup> | 2740 | 3120 |
| Power consumption           | W                 | 50   | 61   |
| Current draw                | A                 | 0.24 | 0.28 |
| Capacitor                   | µF                | 1.5  | 1.5  |
| Capacitor voltage           | VDB               | 400  | 400  |
| Max. back pressure          | Pa                | 200  | 200  |
| Min. ambient temperature    | °C                | -25  | -25  |
| Max. ambient temperature    | °C                | 75   | 75   |
| Starting current            | A                 | 0.53 | 0.53 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change



# AC axial fan

straight blades (A series)

## Technical description


|                                                                            |                                                              |
|----------------------------------------------------------------------------|--------------------------------------------------------------|
| Weight                                                                     | 1.4 kg                                                       |
| Fan size                                                                   | 200 mm                                                       |
| Rotor surface                                                              | Painted black                                                |
| Blade material                                                             | Sheet steel, painted black                                   |
| Number of blades                                                           | 5                                                            |
| Airflow direction                                                          | "V"                                                          |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                        |
| Degree of protection                                                       | IP44; installation- and position-dependent                   |
| Insulation class                                                           | "B"                                                          |
| Moisture (F) / Environmental (H) protection class                          | F1-2                                                         |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                      |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                      |
| Installation position                                                      | Shaft horizontal or rotor on bottom; rotor on top on request |
| Condensation drainage holes                                                | On rotor side                                                |
| Mode                                                                       | S1                                                           |
| Motor storage                                                              | Ball bearing                                                 |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                                    |
| Motor protection                                                           | Thermal overload protector (TOP) internally connected        |
| With cable                                                                 | Variable                                                     |
| Protection class                                                           | I (with customer connection of protective earth)             |
| Conformity with standards                                                  | EN 60335-1; CE                                               |
| Approval                                                                   | CCC; UL 507                                                  |



# AC axial fan

straight blades (A series)

Product drawing



- |   |                                 |
|---|---------------------------------|
| 1 | Direction of air flow "V"       |
| 2 | Max. clearance for screw 5 mm   |
| 3 | Cable AWG20, 4x crimped splices |

Connection diagram




|    |              |   |       |    |       |
|----|--------------|---|-------|----|-------|
| U1 | blue         | Z | brown | U2 | black |
| PE | green/yellow |   |       |    |       |



AC axial fan  
straight blades (A series)

Curves: Air performance 50 Hz



Measurement: LU-57279

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values


|   | U   | f  | n                 | P <sub>e</sub> | I    | qv   | p <sub>is</sub> |
|---|-----|----|-------------------|----------------|------|------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h | Pa              |
| 1 | 230 | 50 | 2740              | 50             | 0.24 | 740  | 0               |
| 2 | 230 | 50 | 2685              | 50             | 0.24 | 670  | 30              |
| 3 | 230 | 50 | 2665              | 52             | 0.24 | 580  | 60              |
| 4 | 230 | 50 | 2680              | 51             | 0.24 | 400  | 88              |

U = Power supply · f = Frequency · n = Speed · P<sub>e</sub> = Power consumption · I = Current draw · qv = Air flow · p<sub>is</sub> = Pressure increase



AC axial fan  
straight blades (A series)

Curves: Air performance 60 Hz



Measurement: LU-57280

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | qv   | p <sub>is</sub> |
|---|-----|----|-------------------|----------------|------|------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h | Pa              |
| 1 | 230 | 60 | 3120              | 61             | 0.28 | 830  | 0               |
| 2 | 230 | 60 | 3045              | 65             | 0.28 | 760  | 40              |
| 3 | 230 | 60 | 3005              | 68             | 0.29 | 650  | 80              |
| 4 | 230 | 60 | 3035              | 66             | 0.29 | 480  | 110             |

U = Power supply · f = Frequency · n = Speed · P<sub>e</sub> = Power consumption · I = Current draw · qv = Air flow · p<sub>is</sub> = Pressure increase

