

A4D350-AN08-20 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142



Nominal data

| | | | |
|-----------------------------|--------------------|------|------|
| Type | A4D350-AN08-20 | | |
| Motor | M4D074-DF | | |
| Phase | | 3~ | 3~ |
| Nominal voltage | VAC | 400 | 400 |
| Wiring | | Y | Y |
| Frequency | Hz | 50 | 60 |
| Method of obtaining data | | ml | ml |
| Valid for approval/standard | | CE | CE |
| Speed (rpm) | min ⁻¹ | 1370 | 1520 |
| Power consumption | W | 170 | 230 |
| Current draw | A | 0.37 | 0.40 |
| Max. back pressure | Pa | 90 | 90 |
| Max. back pressure | inH ₂ O | 0.36 | 0.36 |
| Min. ambient temperature | °C | -25 | -25 |
| Max. ambient temperature | °C | 65 | 55 |
| Starting current | A | 1.1 | 1.1 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

| | | Actual | Req. 2015 | | | |
|-----------------------------------|---|--------|-----------|-------------------------------|-------------------|------|
| 01 Overall efficiency η_{es} | % | 28.7 | 28.6 | 09 Power consumption P_e | kW | 0.16 |
| 02 Measurement category | | A | | 09 Air flow q_v | m ³ /h | 2105 |
| 03 Efficiency category | | Static | | 09 Pressure increase p_{fs} | Pa | 82 |
| 04 Efficiency grade N | | 40.1 | 40 | 10 Speed (rpm) n | min ⁻¹ | 1375 |
| 05 Variable speed drive | | No | | 11 Specific ratio* | | 1.00 |

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = $1 + p_g / 100\,000\text{ Pa}$

LU-131044




Technical description

| | |
|--|--|
| Weight | 3.2 kg |
| Fan size | 350 mm |
| Rotor surface | Painted black |
| Blade material | PP plastic |
| Number of blades | 5 |
| Airflow direction | "V" |
| Direction of rotation | Counterclockwise, viewed toward rotor |
| Degree of protection | IP44; installation- and position-dependent as per EN 60034-5. The degree of protection is only assured when the intended cable guard and terminal box are installed. |
| Insulation class | "F" |
| Moisture (F) / Environmental (H) protection class | F2-2 |
| Max. permitted ambient temp. for motor (transport/storage) | + 80 °C |
| Min. permitted ambient temp. for motor (transport/storage) | - 40 °C |
| Installation position | Shaft horizontal or rotor on bottom; rotor on top on request |
| Condensation drainage holes | On rotor side |
| Mode | S1 |
| Motor bearing | Ball bearing |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA |
| Electrical hookup | Prepared for terminal box installation |
| With cable | Variable |
| Protection class | I (with customer connection of protective earth) |
| Conformity with standards | EN 60335-1 |

AC axial fan

sickle-shaped blades (S series)


Product drawing



| | |
|---|---|
| 1 | Direction of air flow "V" |
| 2 | Max. clearance for screw 10 mm |
| 3 | Max. clearance for screw 8 mm |
| 4 | Cable Dipotherm 4G 0.5 mm ² , 4x crimped splices |




Connection diagram



Change of rotation direction by reversing two phases

| | | | | | |
|----|-------------------|----|-----------------|----|--------------|
| | Three-phase motor | Y | Star connection | L1 | black |
| L2 | blue | L3 | brown | PE | green/yellow |

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-131044-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.


Measured values

| | Wired | U | f | n | P _e | I | LpA _{in} | LwA _{in} | qv | P _{fs} | qv | P _{fs} |
|---|-------|-----|----|-------------------|----------------|------|-------------------|-------------------|-------------------|-----------------|------|--------------------|
| | | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | m ³ /h | Pa | CFM | inH ₂ O |
| 1 | Y | 400 | 50 | 1405 | 136 | 0.34 | 61 | 69 | 3320 | 0 | 1955 | 0.00 |
| 2 | Y | 400 | 50 | 1395 | 148 | 0.35 | 59 | 66 | 2935 | 30 | 1725 | 0.12 |
| 3 | Y | 400 | 50 | 1380 | 158 | 0.35 | 56 | 64 | 2505 | 60 | 1475 | 0.24 |
| 4 | Y | 400 | 50 | 1370 | 170 | 0.37 | 56 | 64 | 1875 | 90 | 1105 | 0.36 |

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
 qv = Air flow · P_{fs} = Pressure increase



Curves: Air performance 60 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-131047-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

| | Wired | U | f | n | P _e | I | LpA _{in} | LwA _{in} | qv | P _{fs} | qv | P _{fs} |
|---|-------|-----|----|-------------------|----------------|------|-------------------|-------------------|-------------------|-----------------|------|--------------------|
| | | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | m ³ /h | Pa | CFM | inH ₂ O |
| 1 | Y | 400 | 60 | 1595 | 184 | 0.33 | 64 | 72 | 3760 | 0 | 2210 | 0.00 |
| 2 | Y | 400 | 60 | 1575 | 200 | 0.35 | 62 | 69 | 3385 | 30 | 1995 | 0.12 |
| 3 | Y | 400 | 60 | 1550 | 215 | 0.37 | 60 | 67 | 2995 | 60 | 1760 | 0.24 |
| 4 | Y | 400 | 60 | 1520 | 230 | 0.40 | 58 | 66 | 2495 | 90 | 1470 | 0.36 |

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
 qv = Air flow · P_{fs} = Pressure increase

