

A8D910-AE01-05 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

Nominal data

Type	A8D910-AE01-05				
Motor	M8D138-LA				
Phase		3~	3~	3~	3~
Nominal voltage	VAC	400	400	400	400
Connection		Δ	Y	Δ	Y
Frequency	Hz	50	50	60	60
Type of data definition		ml	ml	ml	ml
Valid for approval / standard		CE	CE	CE	CE
Speed (rpm)	min ⁻¹	670	515	720	455
Power input	W	910	560	1250	580
Current draw	A	2.27	1.16	2.65	1.3
Max. back pressure	Pa	90	54	108	43
Min. ambient temperature	°C	-40	-40	-40	-40
Max. ambient temperature	°C	80	80	55	55
Starting current	A	6.1	2.0	5.2	1.7

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

		Actual	Request 2015		
01 Overall efficiency η_{es}	%	34.8	33.3	09 Power input P_e	kW 0.88
02 Measurement category	A			09 Air flow q_v	m ³ /h 13940
03 Efficiency category	Static			09 Pressure increase p_{fs}	Pa 80
04 Efficiency grade N	41.5	40		10 Speed (rpm) n	min ⁻¹ 670
05 Variable speed drive	No			11 Specific ratio*	1.00

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.* Specific ratio = $1 + p_g / 100\,000\text{ Pa}$

LU-160563




Technical features

Mass	25.1 kg
Size	910 mm
Surface of rotor	Coated in black
Material of terminal box	Die-cast aluminium, coated in black
Material of blades	Aluminium sheet insert (coated in black), sprayed with PP plastic
Number of blades	5
Blade angle	-5°
Direction of air flow	"V"
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 55
Insulation class	"F"
Humidity (F)/environmental protection class (H)	F4-2
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Any
Condensate discharge holes	On rotor and stator sides
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box
Motor protection	Thermal overload protector (TOP) brought out, basic insulation
Cable exit	Axial
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60034-1 (2010); EN 61800-5-1; CE
Approval	VDE; EAC




Product drawing



1	Direction of air flow "V"
2	Depth of screw max. 18 mm
3	Tightening torque 2.5±0.4 Nm
4	Cable diameter min. 10 mm, max. 12 mm, tightening torque 4±0.6 Nm




Connection screen



Changing the direction of rotation by reversing the two phases

Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2 x grey
PE	green / yellow				

Charts: Air flow 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-160563-1
Measurement: LU-161729-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.


Measured values

	Conn.	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m ³ /h	Pa	cfm	inH ₂ O
1	Δ	400	50	705	617	2.06	64	71	71	21290	0	12530	0.00
2	Δ	400	50	690	730	2.16	62	69	69	18895	30	11120	0.12
3	Δ	400	50	680	825	2.25	60	68	67	16060	60	9455	0.24
4	Δ	400	50	670	910	2.27	64	71	72	12520	90	7370	0.36
5	Y	400	50	600	428	0.93	60	67	66	18480	0	10875	0.00
6	Y	400	50	560	481	1.04	57	64	63	15755	21	9270	0.08
7	Y	400	50	525	519	1.12	54	61	61	12880	39	7580	0.16
8	Y	400	50	515	560	1.16	56	63	63	9705	54	5710	0.22

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed (rpm) · P_e = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side
LwA_{out} = Sound power level outlet side · q_v = Air flow · P_{fs} = Pressure increase



Charts: Air flow 60 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-161731-1
Measurement: LU-161735-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	Conn.	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m ³ /h	Pa	cfm	inH ₂ O
1	Δ	400	60	790	873	2.05	66	74	73	24165	0	14220	0.00
2	Δ	400	60	760	1032	2.30	64	71	71	20825	40	12255	0.16
3	Δ	400	60	725	1166	2.56	62	70	69	16765	80	9870	0.32
4	Δ	400	60	720	1250	2.65	67	74	74	13000	108	7650	0.43
5	Y	400	60	565	493	1.10	59	66	65	18000	0	10595	0.00
6	Y	400	60	500	517	1.16	54	61	60	14385	19	8470	0.08
7	Y	400	60	460	533	1.21	52	58	58	10990	34	6470	0.14
8	Y	400	60	455	580	1.30	53	60	60	8295	44	4885	0.18

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed (rpm) · P_e = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase

