

D1G133-AB29-16

EC centrifugal fan

forward-curved, dual-intake
with housing (without flange)



D1G133-AB29-16 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	D1G133-AB29-16	
Motor	M1G074-BF	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1780
Power consumption	W	105
Current draw	A	5.6
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Technical description


Weight	2.9 kg
Fan size	133 mm
Rotor surface	Painted black
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP42
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F0
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM
Motor protection	Reverse polarity and locked-rotor protection
With cable	Variable
Conformity with standards	EN 60950-1
Approval	CSA C22.2 No. 77; UL 1004-1



EC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Product drawing




1 Cable PVC AWG20, 4x crimped splices

EC centrifugal fan

forward-curved, dual-intake
with housing (without flange)


Connection diagram



No.	Conn.	Designation	Color	Function/assignment
1	1	Un +24 VDC	red	Power supply 24 VDC, maximum ripple 3.5 %
1	2	0-10 VDC	yellow	Control input Re > 100k
1	3	Tach	white	Tach output, 3 pulses per revolution, Isink max = 10 mA
1	4	GND	blue	Reference ground



Curves: Air performance



Measurement: LU-48008-1
Measurement: LU-48007-1
Measurement: LU-48009-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	min ⁻¹	W	A	m ³ /h	Pa	CFM	inH ₂ O
1	28	1895	135	6.24	745	55	440	0.22
2	28	2275	117	5.10	550	184	325	0.74
3	28	2610	108	4.47	390	273	230	1.10
4	28	2995	100	3.99	265	419	155	1.68
5	24	1780	105	5.60	700	50	410	0.20
6	24	2130	96	4.68	515	160	305	0.64
7	24	2440	89	4.17	365	240	215	0.96
8	24	2755	75	3.47	240	340	140	1.36
9	16	1505	62	4.35	575	38	340	0.15
10	16	1735	51	3.53	410	104	240	0.42
11	16	1920	43	2.98	285	145	165	0.58
12	16	2115	35	2.49	180	195	105	0.78

U = Power supply · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase