

# AC centrifugal fan

forward-curved, dual-intake  
with housing (without flange)

D2D133-AB02-36 ebmpapst Datasheet

[sales@fansco.com](mailto:sales@fansco.com)

[www.fansco.com](http://www.fansco.com)

## Nominal data

|                             |                    |      |      |
|-----------------------------|--------------------|------|------|
| Type                        | D2D133-AB02-36     |      |      |
| Motor                       | M2D068-DF          |      |      |
| Phase                       |                    | 3~   | 3~   |
| Nominal voltage             | VAC                | 400  | 400  |
| Wiring                      |                    | Y    | Y    |
| Frequency                   | Hz                 | 50   | 60   |
| Method of obtaining data    |                    | ml   | ml   |
| Valid for approval/standard |                    | CE   | CE   |
| Speed (rpm)                 | min <sup>-1</sup>  | 2170 | 2640 |
| Power consumption           | W                  | 225  | 215  |
| Current draw                | A                  | 0.37 | 0.34 |
| Min. back pressure          | Pa                 | 100  | 250  |
| Min. back pressure          | inH <sub>2</sub> O | 0.4  | 1    |
| Min. ambient temperature    | °C                 | -25  | -25  |
| Max. ambient temperature    | °C                 | 60   | 55   |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · oe = Customer equipment  
Subject to change



# AC centrifugal fan

forward-curved, dual-intake  
with housing (without flange)

## Technical description


|                                                                            |                                                                              |
|----------------------------------------------------------------------------|------------------------------------------------------------------------------|
| Weight                                                                     | 4.8 kg                                                                       |
| Fan size                                                                   | 133 mm                                                                       |
| Rotor surface                                                              | Painted black                                                                |
| Impeller material                                                          | Sheet steel, galvanized and painted black                                    |
| Housing material                                                           | Sheet steel, galvanized                                                      |
| Guard grille material                                                      | Steel, galvanized and coated with white-aluminum plastic (RAL 9006)          |
| Motor suspension                                                           | Motor mounted with brackets on one side                                      |
| Direction of rotation                                                      | Clockwise, viewed toward rotor                                               |
| Degree of protection                                                       | IP54                                                                         |
| Insulation class                                                           | "B"                                                                          |
| Moisture (F) / Environmental (H) protection class                          | F2-2                                                                         |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                                      |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                                      |
| Installation position                                                      | Any                                                                          |
| Condensation drainage holes                                                | On rotor side                                                                |
| Mode                                                                       | S1                                                                           |
| Motor bearing                                                              | Ball bearing                                                                 |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                                                    |
| Electrical hookup                                                          | With plug                                                                    |
| With cable                                                                 | Axial                                                                        |
| Protection class                                                           | I (with customer connection of protective earth)                             |
| Conformity with standards                                                  | EN 60335-1, motor does not have factory-installed overheating protection; CE |



# AC centrifugal fan


forward-curved, dual-intake  
with housing (without flange)

## Product drawing



1 Cable PVC 3X 0.5 mm², 3x flat push-on receptacle 2.8 x 1 crimped

## Connection diagram



Note: Change of rotation direction by reversing two phases


|    |                 |    |       |    |      |
|----|-----------------|----|-------|----|------|
| Y  | Star connection | L1 | black | L2 | blue |
| L3 | brown           |    |       |    |      |



# AC centrifugal fan

forward-curved, dual-intake  
with housing (without flange)

## Curves: Air performance 50 Hz



Measurement: LU-41101-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | qv                | p <sub>fs</sub> | qv  | p <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|-------------------|-----------------|-----|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | Pa              | CFM | inH <sub>2</sub> O |
| 1 | 400 | 50 | 2170              | 225            | 0.37 | 825               | 100             | 485 | 0.40               |
| 2 | 400 | 50 | 2395              | 179            | 0.30 | 655               | 200             | 385 | 0.80               |
| 3 | 400 | 50 | 2580              | 136            | 0.25 | 460               | 260             | 270 | 1.04               |
| 4 | 400 | 50 | 2745              | 92             | 0.21 | 280               | 320             | 165 | 1.28               |


U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · qv = Air flow · p<sub>fs</sub> = Pressure increase



# AC centrifugal fan

forward-curved, dual-intake  
with housing (without flange)

## Curves: Air performance 60 Hz



Measurement: LU-41103-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub> | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|----------------|-----------------|----------------|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h           | Pa              | CFM            | inH <sub>2</sub> O |
| 1 | 400 | 60 | 2640              | 215            | 0.34 | 590            | 250             | 345            | 1.00               |
| 2 | 400 | 60 | 2810              | 185            | 0.30 | 480            | 300             | 285            | 1.20               |
| 3 | 400 | 60 | 3020              | 147            | 0.24 | 355            | 380             | 210            | 1.53               |
| 4 | 400 | 60 | 3235              | 101            | 0.19 | 225            | 460             | 130            | 1.85               |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

