

# AC centrifugal fan

forward-curved, dual-intake

with housing (flange)

D2D133-AB26-33 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

## Nominal data

|                             |                    |      |      |
|-----------------------------|--------------------|------|------|
| Type                        | D2D133-AB26-33     |      |      |
| Motor                       | M2D068-DF          |      |      |
| Phase                       |                    | 3~   | 3~   |
| Nominal voltage             | VAC                | 400  | 400  |
| Wiring                      |                    | Y    | Y    |
| Frequency                   | Hz                 | 50   | 60   |
| Method of obtaining data    |                    | ml   | ml   |
| Valid for approval/standard |                    | CE   | CE   |
| Speed (rpm)                 | min <sup>-1</sup>  | 2150 | 2250 |
| Power consumption           | W                  | 225  | 265  |
| Current draw                | A                  | 0.36 | 0.41 |
| Min. back pressure          | Pa                 | 100  | 150  |
| Min. back pressure          | inH <sub>2</sub> O | 0.4  | 0.6  |
| Min. ambient temperature    | °C                 | -25  | -25  |
| Max. ambient temperature    | °C                 | 70   | 45   |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · oe = Customer equipment  
Subject to change



# AC centrifugal fan

forward-curved, dual-intake  
with housing (flange)

## Technical description


|                                                                            |                                                        |
|----------------------------------------------------------------------------|--------------------------------------------------------|
| Weight                                                                     | 3.5 kg                                                 |
| Fan size                                                                   | 133 mm                                                 |
| Rotor surface                                                              | Painted black                                          |
| Impeller material                                                          | Sheet steel, painted black                             |
| Housing material                                                           | Sheet steel, hot-dip galvanized                        |
| Motor suspension                                                           | Motor vibration-damped on both sides                   |
| Direction of rotation                                                      | Clockwise, viewed toward rotor                         |
| Degree of protection                                                       | IP44; installation- and position-dependent             |
| Insulation class                                                           | "F"                                                    |
| Moisture (F) / Environmental (H) protection class                          | F5                                                     |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                |
| Installation position                                                      | Any                                                    |
| Condensation drainage holes                                                | None                                                   |
| Mode                                                                       | S1                                                     |
| Motor bearing                                                              | Ball bearing                                           |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                              |
| Motor protection                                                           | Thermal overload protector (TOP) with basic insulation |
| Protection class                                                           | I (with customer connection of protective earth)       |
| Conformity with standards                                                  | EN 60335-1; CE                                         |



# AC centrifugal fan

forward-curved, dual-intake  
with housing (flange)

## Product drawing




1 Cable halogen-silicone-free 0.5 mm<sup>2</sup>, 6 x crimped splices



# AC centrifugal fan

forward-curved, dual-intake  
with housing (flange)

## Curves: Air performance 50 Hz Y



Measurement: LU-68644-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | Wired | U   | f  | n                 | P <sub>e</sub> | I    | qv   | p <sub>fs</sub> | qv  | p <sub>fs</sub>    |
|---|-------|-----|----|-------------------|----------------|------|------|-----------------|-----|--------------------|
|   |       | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h | Pa              | CFM | inH <sub>2</sub> O |
| 1 | Y     | 400 | 50 | 2150              | 225            | 0.36 | 780  | 100             | 460 | 0.40               |
| 2 | Y     | 400 | 50 | 2395              | 177            | 0.30 | 620  | 200             | 365 | 0.80               |
| 3 | Y     | 400 | 50 | 2575              | 136            | 0.25 | 445  | 260             | 260 | 1.04               |
| 4 | Y     | 400 | 50 | 2725              | 97             | 0.21 | 280  | 320             | 165 | 1.28               |


Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · qv = Air flow · p<sub>fs</sub> = Pressure increase



# AC centrifugal fan

forward-curved, dual-intake  
with housing (flange)

## Curves: Air performance 60 Hz Y



Measurement: LU-68645-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | Wired | U   | f  | n                 | P <sub>e</sub> | I    | qv   | p <sub>fs</sub> | qv  | p <sub>fs</sub>    |
|---|-------|-----|----|-------------------|----------------|------|------|-----------------|-----|--------------------|
|   |       | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h | Pa              | CFM | inH <sub>2</sub> O |
| 1 | Y     | 400 | 60 | 2250              | 265            | 0.41 | 720  | 150             | 425 | 0.60               |
| 2 | Y     | 400 | 60 | 2585              | 217            | 0.34 | 580  | 240             | 345 | 0.96               |
| 3 | Y     | 400 | 60 | 2810              | 180            | 0.29 | 440  | 320             | 260 | 1.28               |
| 4 | Y     | 400 | 60 | 3095              | 128            | 0.22 | 280  | 420             | 165 | 1.69               |

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · qv = Air flow · p<sub>fs</sub> = Pressure increase

