

AC centrifugal fan

forward-curved, dual-intake

with housing (flange)

D2D160-BE02-12 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	D2D160-BE02-12		
Motor	M2D074-LA		
Phase		3~	3~
Nominal voltage	VAC	230	400
Wiring		Δ	Y
Frequency	Hz	50	50
Method of obtaining data		ml	ml
Valid for approval/standard		-	-
Speed (rpm)	min ⁻¹	2700	2700
Power consumption	W	700	700
Current draw	A	2.2	1.28
Min. back pressure	Pa	400	400
Min. back pressure	inH ₂ O	1.61	1.61
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	75	75
Starting current	A	9.25	5.34

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC centrifugal fan

forward-curved, dual-intake

with housing (flange)

Technical description


Weight	11.2 kg
Fan size	160 mm
Rotor surface	Painted black
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Guard grille material	Steel, galvanized and coated with white-aluminum plastic (RAL 9006)
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP00
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F2-1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Electrical hookup	With plug
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1
Approval	UL 1004-1; CSA C22.2 No. 100



AC centrifugal fan

forward-curved, dual-intake
with housing (flange)

Product drawing




1	Cable PFA AWG20, header Weidmüller STV S 9 SS and 9x crimped splices
1.1	black
1.2	blue
1.3	brown
1.4	gray
1.5	green/yellow
1.6	gray
1.7	green
1.8	white
1.9	yellow

AC centrifugal fan

forward-curved, dual-intake
with housing (flange)

Connection diagram




Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	TOP	2x gray
PE	green/yellow	U2	green	V2	white
W2	yellow				



AC centrifugal fan

forward-curved, dual-intake
with housing (flange)

Curves: Air performance 50 Hz



Measurement: LU-112482-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	Pa	CFM	inH ₂ O
1	400	50	2700	700	1.28	1575	400	925	1.61
2	400	50	2775	564	1.10	1290	500	760	2.01
3	400	50	2825	454	0.96	970	575	570	2.31
4	400	50	2855	387	0.89	705	650	415	2.61

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

