

AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

D2E133-CI33-94 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	D2E133-CI33-94		
Motor	M2E068-CF		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50	60
Method of obtaining data		ml	ml
Valid for approval/standard		-	-
Speed (rpm)	min ⁻¹	1700	2100
Power consumption	W	175	190
Current draw	A	0.77	0.84
Capacitor	μF	4	4
Capacitor voltage	VDB	400	400
Capacitor standard		S2 (CE)	S0 (CE)
Min. back pressure	Pa	50	200
Min. back pressure	inH ₂ O	0.2	0.8
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	35	25
Starting current	A	0.84	0.88

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Technical description


Weight	3.0 kg
Fan size	133 mm
Rotor surface	Unpainted
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, hot-dip galvanized
Support structure material	Sheet steel, hot-dip galvanized
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Axial
Protection class	I (with customer connection of protective earth)
Motor capacitor according to EN 60252-1 in safety protection class	S2
Conformity with standards	EN 60335-1



AC centrifugal fan


forward-curved, dual-intake
with housing (without flange)

Product drawing



1	Cable PVC AWG20, 2x plug pin tyco 163555-8
2	Ground conductor PVC AWG20, 1x ring terminal 21 x 14 x 8.4
3	Ground conductor PVC AWG20, 1x flat push-on receptacle 6.3 x 0.8

Connection diagram




L	red	N	black	PE	green/yellow
---	-----	---	-------	----	--------------

AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Curves: Air performance 50 Hz



Measurement: LU-105286-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	P _{is}	q _v	P _{is}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	230	50	1700	175	0.77	715	50	420	0.20
2	230	50	1900	159	0.69	650	135	385	0.54
3	230	50	2150	146	0.64	550	220	325	0.88
4	230	50	2415	129	0.56	390	300	230	1.20


U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · P_{is} = Pressure increase



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Curves: Air performance 60 Hz



Measurement: LU-105290-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	230	60	2100	190	0.84	515	200	300	0.80
2	230	60	2330	176	0.77	430	265	250	1.06
3	230	60	2535	171	0.75	350	335	205	1.34
4	230	60	2805	161	0.71	190	400	115	1.61

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

