

# AC centrifugal fan

forward-curved, dual-intake

with housing (flange)

## ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

|                             |                   |         |         |
|-----------------------------|-------------------|---------|---------|
| Type                        | D2E146-HT67-31    |         |         |
| Motor                       | M2E068-EC         |         |         |
| Phase                       |                   | 1~      | 1~      |
| Nominal voltage             | VAC               | 230     | 230     |
| Frequency                   | Hz                | 50      | 60      |
| Method of obtaining data    |                   | ml      | ml      |
| Valid for approval/standard |                   | -       | -       |
| Speed (rpm)                 | min <sup>-1</sup> | 1850    | 2100    |
| Power consumption           | W                 | 355     | 400     |
| Current draw                | A                 | 1.55    | 1.75    |
| Capacitor                   | µF                | 8       | 8       |
| Capacitor voltage           | VDB               | 450     | 450     |
| Capacitor standard          |                   | S2 (CE) | S2 (CE) |
| Min. back pressure          | Pa                | 0       | 200     |
| Min. back pressure          | in. wg            | 0       | 0.8     |
| Min. ambient temperature    | °C                | -25     | -25     |
| Max. ambient temperature    | °C                | 55      | 50      |
| Starting current            | A                 | 1.8     | 1.9     |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change



# AC centrifugal fan

forward-curved, dual-intake  
with housing (flange)


## Technical description

|                                                                            |                                                                 |
|----------------------------------------------------------------------------|-----------------------------------------------------------------|
| Weight                                                                     | 3.6 kg                                                          |
| Fan size                                                                   | 146 mm                                                          |
| Rotor surface                                                              | Unpainted                                                       |
| Terminal box material                                                      | PP plastic                                                      |
| Impeller material                                                          | Sheet steel, galvanized                                         |
| Housing material                                                           | PP plastic                                                      |
| Motor suspension                                                           | Motor vibration-damped on both sides                            |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                           |
| Degree of protection                                                       | IP20                                                            |
| Insulation class                                                           | "F"                                                             |
| Moisture (F) / Environmental (H) protection class                          | H0 - dry environment                                            |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                         |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                         |
| Installation position                                                      | Any                                                             |
| Condensation drainage holes                                                | None                                                            |
| Mode                                                                       | S1                                                              |
| Motor bearing                                                              | Ball bearing                                                    |
| Speed levels                                                               | 4                                                               |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                                       |
| Electrical hookup                                                          | Via terminal box, capacitor integrated and connected; With plug |
| Motor protection                                                           | Thermal overload protector (TOP) internally connected           |
| With cable                                                                 | Variable                                                        |
| Protection class                                                           | I (with customer connection of protective earth)                |
| Motor capacitor according to EN 60252-1 in safety protection class         | S2                                                              |
| Conformity with standards                                                  | EN 60335-2-31                                                   |
| Approval                                                                   | VDE; EAC                                                        |



## AC centrifugal fan


## Product drawing



# AC centrifugal fan

forward-curved, dual-intake  
with housing (flange)

## Connection diagram




The switch must interrupt the circuit when switching.

|   |                  |   |        |   |                     |
|---|------------------|---|--------|---|---------------------|
| 1 | Step 1 (min.)    | 2 | Step 2 | 3 | Step 3              |
| 4 | Step 4 (max.)    | 5 | N      | 6 | PE protective earth |
| 7 | Speed increasing |   |        |   |                     |



## Curves: Air performance 50 Hz



Measurement: LU-45713-1  
 Measurement: LU-45715-1  
 Measurement: LU-45717-1  
 Measurement: LU-45719-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.


## Measured values

|    | Stage | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub> | P <sub>fs</sub> | q <sub>v</sub> | P <sub>fs</sub> |
|----|-------|-----|----|-------------------|----------------|------|----------------|-----------------|----------------|-----------------|
|    |       | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h           | Pa              | cfm            | in. wg          |
| 1  | 4     | 230 | 50 | 1850              | 355            | 1.55 | 1060           | 0               | 625            | 0.00            |
| 2  | 4     | 230 | 50 | 2150              | 318            | 1.38 | 930            | 200             | 550            | 0.80            |
| 3  | 4     | 230 | 50 | 2435              | 268            | 1.16 | 700            | 400             | 410            | 1.61            |
| 4  | 4     | 230 | 50 | 2610              | 227            | 0.99 | 450            | 460             | 265            | 1.85            |
| 5  | 3     | 230 | 50 | 1550              | 286            | 1.27 | 855            | 0               | 505            | 0.00            |
| 6  | 3     | 230 | 50 | 1850              | 261            | 1.18 | 790            | 145             | 465            | 0.58            |
| 7  | 3     | 230 | 50 | 2235              | 222            | 1.03 | 640            | 337             | 380            | 1.35            |
| 8  | 3     | 230 | 50 | 2515              | 179            | 0.87 | 430            | 418             | 250            | 1.68            |
| 9  | 2     | 230 | 50 | 1195              | 233            | 1.06 | 640            | 0               | 380            | 0.00            |
| 10 | 2     | 230 | 50 | 1455              | 222            | 1.02 | 610            | 88              | 360            | 0.35            |
| 11 | 2     | 230 | 50 | 1890              | 196            | 0.94 | 540            | 239             | 320            | 0.96            |
| 12 | 2     | 230 | 50 | 2315              | 158            | 0.81 | 395            | 360             | 235            | 1.45            |
| 13 | 1     | 230 | 50 | 875               | 195            | 0.89 | 460            | 0               | 270            | 0.00            |
| 14 | 1     | 230 | 50 | 1055              | 191            | 0.88 | 440            | 45              | 260            | 0.18            |
| 15 | 1     | 230 | 50 | 1420              | 179            | 0.84 | 400            | 132             | 235            | 0.53            |
| 16 | 1     | 230 | 50 | 1965              | 151            | 0.76 | 335            | 255             | 195            | 1.02            |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · P<sub>fs</sub> = Pressure increase



## Curves: Air performance 60 Hz



Measurement: LU-45714-1  
 Measurement: LU-45716-1  
 Measurement: LU-45718-1  
 Measurement: LU-45720-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|    | Stage | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub> | P <sub>fs</sub> | q <sub>v</sub> | P <sub>fs</sub> |
|----|-------|-----|----|-------------------|----------------|------|----------------|-----------------|----------------|-----------------|
|    |       | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h           | Pa              | cfm            | in. wg          |
| 1  | 4     | 230 | 60 | 2100              | 400            | 1.75 | 875            | 200             | 515            | 0.80            |
| 2  | 4     | 230 | 60 | 2360              | 384            | 1.67 | 780            | 350             | 460            | 1.41            |
| 3  | 4     | 230 | 60 | 2685              | 360            | 1.58 | 620            | 500             | 365            | 2.01            |
| 4  | 4     | 230 | 60 | 2935              | 335            | 1.48 | 350            | 575             | 205            | 2.31            |
| 5  | 3     | 230 | 60 | 1780              | 296            | 1.37 | 740            | 143             | 435            | 0.57            |
| 6  | 3     | 230 | 60 | 2085              | 284            | 1.34 | 690            | 273             | 405            | 1.10            |
| 7  | 3     | 230 | 60 | 2495              | 260            | 1.29 | 575            | 432             | 335            | 1.73            |
| 8  | 3     | 230 | 60 | 2870              | 226            | 1.22 | 345            | 552             | 200            | 2.22            |
| 9  | 2     | 230 | 60 | 1325              | 228            | 1.10 | 540            | 75              | 315            | 0.30            |
| 10 | 2     | 230 | 60 | 1560              | 222            | 1.09 | 510            | 148             | 300            | 0.59            |
| 11 | 2     | 230 | 60 | 1990              | 210            | 1.07 | 450            | 268             | 265            | 1.08            |
| 12 | 2     | 230 | 60 | 2575              | 181            | 1.02 | 305            | 439             | 180            | 1.76            |
| 13 | 1     | 230 | 60 | 950               | 187            | 0.92 | 385            | 38              | 225            | 0.15            |
| 14 | 1     | 230 | 60 | 1105              | 185            | 0.91 | 360            | 74              | 215            | 0.30            |
| 15 | 1     | 230 | 60 | 1400              | 180            | 0.90 | 325            | 137             | 190            | 0.55            |
| 16 | 1     | 230 | 60 | 1985              | 165            | 0.88 | 240            | 265             | 140            | 1.06            |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · P<sub>fs</sub> = Pressure increase

