

EC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

D3G120-AA03-10 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	D3G120-AA03-10	
Motor	M3G055-BI	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	1950
Power consumption	W	83
Current draw	A	0.74
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Technical description


Weight	3 kg
Size	120 mm
Motor size	55
Rotor surface	Thick-film passivated
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Fault output (open collector) - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Connector with cable
Motor protection	Electronic motor protection
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE



EC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Product drawing




1	Cable PVC AWG22
	4-pole connector housing TE 350779-5, 4x plug pin TE 926886-1
1.1	+10 V (red)
1.2	GND (blue)
1.3	0-10 V PWM (yellow)
1.4	Fan good / fan bad (white)
2	Cable PVC AWG20
	3-pole connector housing TE 2178473-3, 3x plug pin TE 926887-1
2.1	PE (green/yellow)
2.2	N (blue)
2.3	L (black)

EC centrifugal fan


forward-curved, dual-intake
with housing (without flange)

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	CON10	L	black	Power supply 230 VAC, 50-60 Hz, see nameplate for voltage range
	CON11	N	blue	Neutral conductor
	CON12	PE	green/yellow	Protective earth
	1	GND	blue	GND connection for control interface
	2	0- 10V PWM	yellow	Control input 0-10 V or PWM, electrically isolated
	3	10V/ max 1.1mA	red	Voltage output 10 V / 1.1 mA, electrically isolated, not short-circuit-proof.
	4	FG/FB	white	Fan good / fan bad: open collector, fan good = high, electrically isolated, Isink max = 10 mA

Curves: Air performance 50 Hz



Measurement: LU-158421-1
Measurement: LU-158652-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	m³/h	Pa	cfm	in. wg
1	230	50	1950	83	0.74	58	505	0	295	0.00
2	230	50	2465	82	0.70	57	405	200	240	0.80
3	230	50	2970	81	0.69	59	295	360	170	1.45
4	230	50	3245	66	0.57	60	175	420	105	1.69
5	230	50	1845	67	0.59		475	0	280	0.00
6	230	50	2115	51	0.45		345	147	205	0.59
7	230	50	2325	39	0.39		230	218	135	0.88
8	230	50	2470	31	0.31		135	249	80	1.00
9	230	50	1600	44	0.39		410	0	240	0.00
10	230	50	1600	22	0.20		265	84	155	0.34
11	230	50	1600	13	0.13		155	104	90	0.42
12	230	50	1600	9.0	0.08		85	105	50	0.42

U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · q_v = Air flow · p_{fs} = Pressure increase