D3G133-LV13-01

EC centrifugal fan

forward-curved, dual-intake

with housing (flange)

D3G133-LV13-01 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	**D3G133-LV13-01**
Motor	**M3G055-DF**

Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min^{-1}	2220
Power consumption	W	182
Current draw	A	1.4
Min. back pressure	Pa	0
Min. back pressure	inH2O	0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	34.2	32.1
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		46.1	44
05 Variable speed drive		Yes	

09 Power consumption P_{ed}	kW	0.13
09 Air flow q_v	m^3/h	480
09 Pressure increase p_{fs}	Pa	298
10 Speed (rpm) n	min^{-1}	2725
11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = 1 + p_{fs} / 100 000 Pa

LU-134371

EC centrifugal fan

forward-curved, dual-intake

with housing (flange)

Technical description

Weight	2.7 kg
Fan size	133 mm
Impeller material	Sheet steel, galvanized
Housing material	PP plastic
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	Motor IP54, electronics IP20; installation- and position-dependent
Insulation class	"F"
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from supply - Thermal overload protection for motor
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-4 (industrial environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	With plug
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE

D3G133-LV13-01 ebmpapst Datasheet FansCo sales@fansco.com www.fansco.com

EC centrifugal fan

forward-curved, dual-intake

with housing (flange)

Product drawing



1	Header Molex Micro Fit 3.0 04365 00400 (pluggable with 04364 50400)
1.1	10 V
1.2	Tach
1.3	0-10 V lin. / PWM
1.4	GND
2	Connector Lumberg 3642 03 K01 (pluggable with 3626 03 K01)
2.1	PE
2.2	L
2.3	N
3	4x sheet metal nut for thread EN ISO 1478-ST4.8 (min. screw length 14.5 mm plus material thickness of attachment)

EC centrifugal fan

forward-curved, dual-intake

with housing (flange)

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
CON10	10.1	PE	green/yellow	Protective earth
CON10	10.2	L	black	Power supply 230 VAC, 50-60 Hz, see nameplate for voltage range
CON10	10.3	N	blue	Neutral conductor
CON11	11.1	10 V/max. 1.1 mA	red	Voltage output 10 V, 1.1 mA, electrically isolated, not short-circuit-proof
CON11	11.2	Tach	white	Tach output: Open collector, 1 pulse per revolution, electrically isolated, Isink max = 10 mA
CON11	11.3	0-10 V PWM	yellow	Control input 0-10 V or PWM, electrically isolated
CON11	11.4	GND	blue	GND connection for control interface

D3G133-LV13-01 ebmpapst Datasheet FansCo sales@fansco.com www.fansco.com

EC centrifugal fan

forward-curved, dual-intake

with housing (flange)

Curves: Air performance 50 Hz



Measurement: LU-134371-1
Measurement: LU-134373-1
Measurement: LU-134376-1
Measurement: LU-134377-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P_{ed}	I	LpA_{in}	LwA_{in}	qv	p_{fs}	qv	p_{fs}
	V	Hz	min^{-1}	W	A	dB(A)	dB(A)	m^3/h	Pa	CFM	inH2O
1	230	50	2220	182	1.40	63	76	960	0	565	0.00
2	230	50	2455	182	1.40	63	75	810	160	475	0.64
3	230	50	2695	159	1.25	62	74	600	280	355	1.12
4	230	50	2710	100	0.81	61	72	330	320	195	1.28
5	230	50	2105	167	1.28			930	0	545	0.00
6	230	50	2250	139	1.09			740	135	435	0.54
7	230	50	2405	110	0.87			535	223	315	0.90
8	230	50	2545	82	0.68			310	282	180	1.13
9	230	50	1715	87	0.72			755	0	445	0.00
10	230	50	1825	71	0.61			605	90	355	0.36
11	230	50	1925	58	0.50			430	142	250	0.57
12	230	50	2025	45	0.38			245	178	145	0.71
13	230	50	1310	39	0.34			560	0	330	0.00
14	230	50	1365	32	0.29			440	48	260	0.19
15	230	50	1420	25	0.23			315	77	185	0.31
16	230	50	1480	20	0.19			180	93	105	0.37

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
qv = Air flow · p_{fs} = Pressure increase

D3G133-LV13-01 ebmpapst Datasheet FansCo sales@fansco.com www.fansco.com