

AC centrifugal fan

forward-curved

with housing (large flange)

D4D225-CC11-25 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	D4D225-CC11-25		
Motor	M4D074-LA		
Phase		3~	3~
Nominal voltage	VAC	500	500
Wiring		Y	Y
Frequency	Hz	50	60
Method of obtaining data		ml	ml
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	1050	1250
Power consumption	W	730	665
Current draw	A	1	0.95
Min. back pressure	Pa	50	250
Min. back pressure	in. wg	0.2	1
Max. ambient temperature	°C	35	35
Starting current	A	2	1.85

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · oe = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_e	%	43.3	39.7	09 Power consumption P_e	kW	0.34
02 Measurement category		B		09 Air flow q_v	m ³ /h	1605
03 Efficiency category		Total		09 Pressure increase p_f	Pa	335
04 Efficiency grade N		52.6	49	10 Speed (rpm) n	min ⁻¹	1330
05 Variable speed drive		No		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = $1 + p_f / 100\,000\text{ Pa}$

LU-44361



AC centrifugal fan

forward-curved

with housing (large flange)

Technical description


Weight	12.1 kg
Size	225 mm
Motor size	74
Rotor surface	Painted black
Impeller material	Sheet steel, hot-dip galvanized
Housing material	Sheet steel, hot-dip galvanized
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP22
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0+
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1



AC centrifugal fan


forward-curved
with housing (large flange)

Product drawing



1 Cable silicone, crimped splices

Connection diagram




U1	blue	Z	brown	U2	black
PE	green/yellow				



AC centrifugal fan

forward-curved
with housing (large flange)

Curves: Air performance 50 Hz



Measurement: LU-44361-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	500	50	1050	730	1.00	3195	50	1880	0.20
2	500	50	1135	616	0.89	2805	150	1650	0.60
3	500	50	1235	485	0.74	2295	250	1350	1.00
4	500	50	1360	301	0.55	1350	340	795	1.36

U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase




AC centrifugal fan

forward-curved

with housing (large flange)

Curves: Air performance 60 Hz



Measurement: LU-44363-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	500	60	1250	665	0.95	2450	250	1445	1.00
2	500	60	1385	555	0.78	2000	350	1175	1.41
3	500	60	1520	415	0.61	1400	425	825	1.71
4	500	60	1585	342	0.53	1000	450	590	1.81

U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

