

AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

D4D250-AA02-05 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	D4D250-AA02-05				
Motor	M4D094-LA				
Phase		3~	3~	3~	3~
Nominal voltage	VAC	254	277	440	480
Wiring		Δ	Δ	Y	Y
Frequency	Hz	50	60	50	60
Method of obtaining data		ml	ml	ml	ml
Valid for approval/standard		CE	CE	CE	CE
Speed (rpm)	min ⁻¹	1320	1640	1320	1640
Power consumption	W	1000	950	1000	950
Current draw	A	3.12	2.77	1.8	1.6
Min. back pressure	Pa	260	500	260	500
Min. back pressure	in. wg	1.04	2.01	1.04	2.01
Min. ambient temperature	°C	-40	-40	-40	-40
Max. ambient temperature	°C	45	50	45	50
Starting current	A	10.0	10.2	5.8	5.86

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	40.4	35.9	09 Power consumption P_e	kW	0.52
02 Measurement category		A		09 Air flow q_v	m³/h	2005
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	381
04 Efficiency grade N		48.5	44	10 Speed (rpm) n	min ⁻¹	1405
05 Variable speed drive		No		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-73522



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Technical description


Weight	15.73 kg
Size	250 mm
Motor size	94
Terminal box material	PP plastic
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60034-1 (2010); CE
Approval	EAC



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Product drawing




- | | |
|---|--|
| 1 | Tightening torque 1.5 ± 0.2 Nm |
| 2 | Cable diameter min. 6 mm, max. 12 mm, tightening torque 2 ± 0.3 Nm |

AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Connection diagram




Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2x gray
PE	green/yellow				



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-73522-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	Y	400	50	1240	1140	2.10	70	85	4015	0	2365	0.00
2	Y	400	50	1290	958	1.84	68	82	3540	125	2085	0.50
3	Y	400	50	1340	775	1.56	65	79	2970	250	1745	1.00
4	Y	400	50	1390	589	1.31	62	76	2260	360	1330	1.45


Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · P_{fs} = Pressure increase



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Curves: Air performance 60 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-133126-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	Y	400	60	1410	1210	2.20	67	82	3255	250	1915	1.00
2	Y	400	60	1480	1029	1.82	66	80	2920	350	1720	1.41
3	Y	400	60	1545	875	1.57	65	79	2515	440	1480	1.77
4	Y	400	60	1620	676	1.28	64	78	1935	500	1140	2.01

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{fs} = Pressure increase

