

AC centrifugal fan

forward-curved, dual-intake
with housing (large flange)



D4D250-CA02-11 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	D4D250-CA02-11		
Motor	M4D094-LA		
Phase		3~	3~
Nominal voltage	VAC	230	400
Wiring		Δ	Y
Frequency	Hz	50	50
Method of obtaining data		ml	ml
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	1200	1200
Power consumption	W	1270	1270
Current draw	A	3.98	2.3
Min. back pressure	Pa	50	50
Min. back pressure	in. wg	0.2	0.2
Min. ambient temperature	°C	-40	-40
Max. ambient temperature	°C	45	45
Starting current	A	7.96	4.6

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_e	%	46.2	41	09 Power consumption P_e	kW	0.53
02 Measurement category		B		09 Air flow q_v	m ³ /h	2190
03 Efficiency category		Total		09 Pressure increase p_f	Pa	411
04 Efficiency grade N		54.2	49	10 Speed (rpm) n	min ⁻¹	1400
05 Variable speed drive		No		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = $1 + p_f / 100\,000\text{ Pa}$

LU-42113



AC centrifugal fan

forward-curved, dual-intake
with housing (large flange)

Technical description


Weight	17.3 kg
Size	250 mm
Motor size	94
Rotor surface	Cast in aluminum
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60034-1 (2004); CE
Approval	EAC



AC centrifugal fan

forward-curved, dual-intake
with housing (large flange)

Product drawing




1 Cable Dipotherm 0.5 mm², 9x crimped splices

AC centrifugal fan

forward-curved, dual-intake
with housing (large flange)

Connection diagram



Note: Change of rotation direction by reversing two phases


Δ	Delta connection	Y	Star connection	L1	black
L2	blue	L3	brown	U1	black
V1	blue	W1	brown	U2	green
V2	white	W2	yellow	TOP	gray



AC centrifugal fan

forward-curved, dual-intake
with housing (large flange)

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-42113-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	Y	400	50	1200	1270	2.30	4035	50	2375	0.20
2	Y	400	50	1280	1007	1.87	3495	200	2055	0.80
3	Y	400	50	1330	830	1.60	3130	300	1845	1.20
4	Y	400	50	1395	558	1.25	2250	370	1325	1.49

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · P_{fs} = Pressure increase

