

AC centrifugal fan

forward-curved
with housing and mounting bracket

D4E225-AC15-23 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	D4E225-AC15-23	
Motor	M4E074-LA	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Method of obtaining data		ml
Valid for approval/standard		CE
Speed (rpm)	min ⁻¹	1100
Power consumption	W	430
Current draw	A	1.88
Capacitor	µF	14
Capacitor voltage	VDB	400
Capacitor standard		P2 (CE)
Min. back pressure	Pa	150
Min. back pressure	inH2O	0.6
Max. ambient temperature	°C	50
Starting current	A	2.6

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	34.6	34.6
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		44	44
05 Variable speed drive		No	

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_e	kW	0.33
09 Air flow q_v	m³/h	1500
09 Pressure increase p_{fs}	Pa	273
10 Speed (rpm) n	min ⁻¹	1290
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-78330



AC centrifugal fan

forward-curved

with housing and mounting bracket

Technical description


Weight	11.6 kg
Fan size	225 mm
Rotor surface	Painted black
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP22
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F2-1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Electrical hookup	Capacitor mounted
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE



AC centrifugal fan


forward-curved
with housing and mounting bracket

Product drawing



1 Cable ETFE AWG20, 3x crimped splices

Connection diagram




L	blue	N	black	PE	green/yellow
---	------	---	-------	----	--------------



AC centrifugal fan

forward-curved
with housing and mounting bracket

Curves: Air performance 50 Hz



Measurement: LU-78330-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH ₂ O
1	230	50	1100	430	1.88	1995	150	1175	0.60
2	230	50	1220	377	1.65	1720	240	1015	0.96
3	230	50	1315	319	1.43	1355	300	800	1.20
4	230	50	1370	267	1.25	900	330	530	1.32

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

