

AC centrifugal fan

forward-curved, dual-intake

with housing (flange)

D4E225-BC01-28 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	D4E225-BC01-28	
Motor	M4E074-LA	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Method of obtaining data		ml
Valid for approval/standard		-
Speed (rpm)	min ⁻¹	1100
Power consumption	W	700
Current draw	A	3.05
Capacitor	μF	25
Capacitor voltage	VDB	400
Capacitor standard		S2 (CE)
Min. back pressure	Pa	20
Min. back pressure	inH ₂ O	0.08
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	50
Starting current	A	4.5

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC centrifugal fan

forward-curved, dual-intake
with housing (flange)

Technical description


Weight	11.9 kg
Fan size	225 mm
Rotor surface	Painted black
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Support structure material	Sheet steel, galvanized
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP22
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F2-1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1
Approval	EAC



AC centrifugal fan

forward-curved, dual-intake
with housing (flange)

Product drawing




- | | |
|---|---|
| 1 | Cable ETFE 5x AWG20 |
| 2 | Cable ETFE AWG20, 2x flat push-on receptacle 6.3 x 0.8, 2x insulating sleeve SES 105-01 |

AC centrifugal fan

forward-curved, dual-intake
with housing (flange)

Connection diagram




L	blue	Z	brown	U2	black
N	black	PE	green/yellow	TOP	2x gray



AC centrifugal fan

forward-curved, dual-intake
with housing (flange)

Curves: Air performance 50 Hz



Measurement: LU-105284-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	230	50	1100	700	3.05	3015	20	1775	0.08
2	230	50	1290	602	2.72	2475	200	1455	0.80
3	230	50	1360	504	2.35	1885	300	1110	1.20
4	230	50	1410	425	2.06	1225	350	720	1.41

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

