

AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

D4E240-AA01-04 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	D4E240-AA01-04	
Motor	M4E094-IF	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Method of obtaining data		ml
Valid for approval/standard		CE
Speed (rpm)	min ⁻¹	1380
Power consumption	W	635
Current draw	A	3.0
Capacitor	µF	16
Capacitor voltage	VDB	400
Capacitor standard		S2 (CE)
Min. back pressure	Pa	285
Min. back pressure	in. wg	1.14
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	80

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	35.9	35.9
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		44	44
05 Variable speed drive		No	

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_e	kW	0.52
09 Air flow q_v	m³/h	1810
09 Pressure increase p_{fs}	Pa	358
10 Speed (rpm) n	min ⁻¹	1410
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-153817



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Technical description


Weight	14.1 kg
Size	240 mm
Motor size	94
Impeller material	Sheet steel, galvanized and painted black
Housing material	Sheet steel, galvanized and painted black
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP44
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H2
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Connector with cable
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Lateral
Protection class	I (with customer connection of protective earth)
Motor capacitor according to EN 60252-1 in safety protection class	S2
Conformity with standards	EN 60034-1 (2010)
Approval	EAC



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Product drawing




1	Cable PFA AWG18
	3-pole connector housing TE 350766-4, 3x plug pin TE 926885-1
	2x splice
1.1	PE
1.2	U1
1.3	U2
1.4	2x TOP (gray)



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Connection diagram




U1	blue	Z	brown	U2	black
PE	green/yellow	TOP	2x gray		



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-153817-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	1~	230	50	1380	635	3.00	2260	285	1330	1.14
2	1~	230	50	1400	557	2.67	1955	340	1150	1.36
3	1~	230	50	1420	475	2.36	1500	380	885	1.53

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

