

G1G126-AA49-55

EC centrifugal fan

forward-curved, single-intake
with housing (flange), Gas blower for condensing boilers



G1G126-AA49-55 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	G1G126-AA49-55	
Motor	M1G055-BD	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	187 .. 244
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	5000
Power consumption	W	75
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	70

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC centrifugal fan

forward-curved, single-intake

with housing (flange), Gas blower for condensing boilers

Technical description

Weight	1.4 kg
Fan size	126 mm
Rotor surface	Thick-film passivated
Cover material	PP plastic
Impeller material	PA plastic
Housing material	Die-cast aluminum
Number of blades	18
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP20
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Mode	S1
Premixing	Suitable for premixing.
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limitation - PWM control input
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Reverse polarity and locked-rotor protection
Protection class	I (if protective earth is connected by customer to the housing's connection point)
Conformity with standards	EN 60335-1; CE
Approval	EAC
Comment	Complete unit must be tested for required approvals.




EC centrifugal fan

forward-curved, single-intake

with housing (flange), Gas blower for condensing boilers

Product drawing




1	Housing side parts sealed with NBR round cord (pentane-resistant)
2	Cable PVC 3G 0.5 mm ² with connector housing AMP no. 350766-4 and 3x plug pin AMP no. 926885-1 crimped
2.1	L (brown)
2.2	PE (green/yellow)
2.3	N (blue)
3	Pressure tap possible

EC centrifugal fan

forward-curved, single-intake

with housing (flange), Gas blower for condensing boilers


Connection diagram



EC centrifugal fan

forward-curved, single-intake
with housing (flange), Gas blower for condensing boilers

Curves: Air performance 50 Hz



Measurement: LU-109711-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	q _v	p _{is}	q _v	p _{is}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	230	50	5000	75	0.50	130	0	75	0.00
2	230	50	5520	67	0.47	100	600	60	2.41
3	230	50	5860	61	0.42	80	1000	45	4.01
4	230	50	6165	53	0.36	55	1300	35	5.22

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{is} = Pressure increase

