

EC centrifugal fan

backward-curved, single-intake
with housing (flange)

G1G126-AC13-24 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	G1G126-AC13-24	
Motor	M1G055-AI	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	4450
Power consumption	W	50
Current draw	A	2.35
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	70

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC centrifugal fan

backward-curved, single-intake
with housing (flange)

Technical description


Weight	1.4 kg
Fan size	126 mm
Cover material	PP plastic
Impeller material	PA plastic
Housing material	Die-cast aluminum
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP20; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Cooling hole/opening	On rotor side
Mode	S1
Premixing	Suitable for premixing.
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limitation - PWM control input
Motor protection	Locked-rotor protection
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1
Comment	Complete unit must be tested for required approvals.



EC centrifugal fan

backward-curved, single-intake
with housing (flange)

Product drawing




1	Housing side parts sealed with NBR round cord (pentane-resistant)
2	5-pole header; mating connector (not included in scope of delivery): Lonco, TJC4203-5AW
2.1	(+)
2.2	Speed monitoring
2.3	not used
2.4	PWM input
2.5	(-)
3	Pressure tap sealed (drilled open if required)


EC centrifugal fan

backward-curved, single-intake
with housing (flange)

Connection diagram



Curves: Air performance



Measurement: LU-54513-1
Measurement: LU-54512-1
Measurement: LU-54514-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	min ⁻¹	W	A	m ³ /h	Pa	cfm	inH ₂ O
1	28	4810	62	2.62	125	0	75	0.00
2	28	5290	56	2.29	95	608	55	2.44
3	28	5820	49	1.96	65	1097	40	4.40
4	28	6280	40	1.62	40	1354	25	5.44
5	24	4450	50	2.35	115	0	70	0.00
6	24	4850	43	2.02	85	500	50	2.01
7	24	5255	36	1.69	60	900	35	3.61
8	24	5645	30	1.39	35	1100	20	4.42
9	16	3475	23	1.63	90	0	55	0.00
10	16	3710	20	1.40	65	289	40	1.16
11	16	3965	17	1.19	45	516	25	2.07
12	16	4200	14	1.01	25	601	15	2.41

U = Power supply · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase