

EC centrifugal fan

backward-curved, single-intake
with housing (flange), Gas blower for condensing boilers

G1G144-AG43-05 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	G1G144-AG43-05	
Motor	M1G055-BD	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	4020
Power consumption	W	43
Current draw	A	2.0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC centrifugal fan

backward-curved, single-intake

with housing (flange), Gas blower for condensing boilers

Technical description

Weight	1.8 kg
Fan size	144 mm
Rotor surface	Thick-film passivated
Cover material	PP plastic
Impeller material	PA plastic
Housing material	Die-cast aluminum
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP20
Insulation class	"B"
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None
Cooling hole/opening	On rotor side
Mode	S1
Premixing	Not suitable for premixing.
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM
Electrical hookup	With plug
Motor protection	Reverse polarity and locked-rotor protection
With cable	Lateral
Protection class	I (if protective earth is connected by customer to the housing's connection point)
Conformity with standards	EN 60335-1, motor does not have factory-installed overheating protection
Comment	Complete unit must be tested for required approvals.




EC centrifugal fan

backward-curved, single-intake

with housing (flange), Gas blower for condensing boilers

Product drawing



1	Housing side parts sealed with NBR round cord (pentane-resistant)
2	Cable PVC AWG20 with 6-pole connector housing tyco 350781-1, 4x plug pin tyco 926885-1
2.1	UN +24 VDC
2.2	GND
2.3	0-10 VDC
2.4	Tach
2.5	not used
2.6	not used
3	Pressure tap sealed (drilled open if required)

EC centrifugal fan


backward-curved, single-intake

with housing (flange), Gas blower for condensing boilers


Connection diagram

Customer circuit

Full speed




Adjustable speed




10 V → n = max
 1 V → n = min
 < 1 V → n = 0
 Safe start
 at Unom -30%
 from 4 V Ucontr.

Speed adjustable with fixed resistor




Speed adjustable via PWM 1-10 kHz




100% PWM → n = max
 10% PWM → n = min
 < 10% PWM → n = 0
 Safe start
 at Unom -30%
 from 40% PWM

Set value requirement via temperature controller



Connection

Fan / Motor




No.	Conn.	Designation	Color	Function/assignment
1	1	GND	blue	Reference ground
1	2	Tach	white	Tach output, 2 pulses per revolution, Isink max = 10 mA
1	3	0-10 VDC	yellow	Control input Re > 100k
1	4	Un +24 VDC	red	Power supply 24 VDC, maximum ripple 3.5%

EC centrifugal fan

backward-curved, single-intake

with housing (flange), Gas blower for condensing boilers

Curves: Air performance



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-72264-1

Measurement: LU-72262-1

Measurement: LU-72266-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	qv	p _{fs}	qv	p _{fs}
	V	min ⁻¹	W	A	m ³ /h	Pa	CFM	inH ₂ O
1	28	4320	53	2.23	170	0	100	0.00
2	28	4475	51	2.14	140	353	80	1.42
3	28	4740	49	2.00	105	716	60	2.87
4	28	5145	43	1.73	65	1053	35	4.23
5	24	4020	43	2.00	160	0	95	0.00
6	24	4135	41	1.94	130	300	75	1.20
7	24	4330	38	1.78	95	600	55	2.41
8	24	4595	33	1.52	55	850	35	3.41
9	16	3115	20	1.37	125	0	70	0.00
10	16	3175	19	1.30	100	176	60	0.71
11	16	3270	17	1.19	70	331	40	1.33
12	16	3430	15	1.03	40	473	25	1.90

U = Power supply · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

