

EC centrifugal fan

forward-curved, single-intake
with housing (flange)



G1G160-BD29-52 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	G1G160-BD29-52	
Motor	M1G074-BF	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Frequency	Hz	-
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	1800
Power consumption	W	105
Current draw	A	5.45
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Technical description


Weight	2.7 kg
Fan size	160 mm
Rotor surface	Painted black
Impeller material	Sheet steel, galvanized
Housing material	Die-cast aluminum
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP42
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F0
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM
Motor protection	Reverse polarity and locked-rotor protection
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60950-1
Approval	UL 1004-1; CSA C22.2 No. 77



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Product drawing




1 Cable PVC AWG20, 4x crimped splices

EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
1	1	Un +24 VDC	red	Power supply 24 VDC, maximum ripple 3.5 %
1	2	0-10 VDC	yellow	Control input Re > 100k
1	3	Tach	white	Tach output, 3 pulses per revolution, Isink max = 10 mA
1	4	GND	blue	Reference ground



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Curves: Air performance



Measurement: LU-50792-1
Measurement: LU-50791-1
Measurement: LU-50793-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	qv	p _{fs}	qv	p _{fs}
	V	min ⁻¹	W	A	m³/h	Pa	CFM	inH2O
1	28	1930	129	6.02	550	0	325	0.00
2	28	2160	119	5.31	455	228	270	0.92
3	28	2485	109	4.63	340	457	200	1.83
4	28	2815	103	4.18	235	588	140	2.36
5	24	1800	105	5.45	515	0	305	0.00
6	24	2030	98	4.85	425	200	250	0.80
7	24	2350	91	4.30	315	400	185	1.61
8	24	2600	82	3.81	215	500	125	2.01
9	16	1510	60	4.23	430	0	250	0.00
10	16	1660	53	3.69	345	132	205	0.53
11	16	1845	45	3.10	250	245	145	0.98
12	16	2005	38	2.68	165	295	100	1.18

U = Power supply · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

