

EC centrifugal fan

forward-curved, single-intake
with housing (flange)

G1G160-BH29-13 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	G1G160-BH29-13	
Motor	M1G074-BF	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	1750
Power consumption	W	105
Current draw	A	5.8
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Technical description


Weight	2.7 kg
Size	160 mm
Motor size	74
Rotor surface	Painted black
Impeller material	Sheet steel, galvanized
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1+; F4-1
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM
Motor protection	Reverse polarity and locked-rotor protection
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60950-1
Approval	CSA C22.2 No. 77; UL 1004-1



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Product drawing



1	Cable PVC AWG20, 4x crimped splices
---	-------------------------------------


EC centrifugal fan

forward-curved, single-intake
with housing (flange)


Connection diagram

Customer circuit

Full speed




Adjustable speed




10 V → n = max
1 V → n = min
< 1 V → n = 0
Safe start
at Unom -30%
from 4 V Ucontr.

Speed adjustable via potentiometer




Speed adjustable via PWM 1-10 kHz



100% PWM → n = max
10% PWM → n = min
< 10% PWM → n = 0
Safe start
at Unom -30%
from 40% PWM


Set value requirement via temperature controller



T < 10 °C → n = 0
T > 45 °C → n = max

Connection

Fan / Motor




No.	Conn.	Designation	Color	Function/assignment
1	1	Un +24 VDC	red	Power supply 24 VDC, maximum ripple 3.5 %
1	2	0-10 VDC	yellow	Control input Re > 100k
1	3	Tach	white	Tach output, 3 pulses per revolution, Isink max = 10 mA
1	4	GND	blue	Reference ground

EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Curves: Air performance



Measurement: LU-59980-1
Measurement: LU-59979-1
Measurement: LU-59981-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	28	1870	134	6.43	540	0	320	0.00
2	28	2115	121	5.54	450	229	265	0.92
3	28	2420	110	4.82	340	456	200	1.83
4	28	2825	102	4.20	200	645	120	2.59
5	24	1750	105	5.80	505	0	300	0.00
6	24	1990	99	5.02	420	200	250	0.80
7	24	2275	91	4.43	320	400	190	1.61
8	24	2655	83	3.86	185	550	110	2.21
9	16	1485	63	4.48	425	0	250	0.00
10	16	1670	57	4.01	350	138	205	0.55
11	16	1860	49	3.42	260	263	150	1.06
12	16	2085	41	2.85	145	334	85	1.34

U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

