

# AC centrifugal fan

forward-curved, single-intake

with housing (flange)

G2D180-AE02-14 ebmpapst Datasheet FansCo

sales@fansco.com

www.fansco.com

## Nominal data

|                             |                   |          |
|-----------------------------|-------------------|----------|
| Type                        | G2D180-AE02-14    |          |
| Motor                       | M2D068-GA         |          |
| Phase                       |                   | 3~       |
| Nominal voltage             | VAC               | 230      |
| Wiring                      |                   | $\Delta$ |
| Frequency                   | Hz                | 50       |
| Method of obtaining data    |                   | ml       |
| Valid for approval/standard |                   | CE       |
| Speed (rpm)                 | min <sup>-1</sup> | 2370     |
| Power consumption           | W                 | 420      |
| Current draw                | A                 | 1.12     |
| Min. back pressure          | Pa                | 300      |
| Min. back pressure          | in. wg            | 1.2      |
| Min. ambient temperature    | °C                | -25      |
| Max. ambient temperature    | °C                | 50       |
| Starting current            | A                 | 1.66     |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change

## Data according to Commission Regulation (EU) 327/2011

|                                   | Actual | Req. 2015 |
|-----------------------------------|--------|-----------|
| 01 Overall efficiency $\eta_{es}$ | % 37.4 | 33.6      |
| 02 Measurement category           | A      |           |
| 03 Efficiency category            | Static |           |
| 04 Efficiency grade N             | 47.8   | 44        |
| 05 Variable speed drive           | No     |           |

Data obtained at optimum efficiency level.  
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

|                               |                   |      |
|-------------------------------|-------------------|------|
| 09 Power consumption $P_e$    | kW                | 0.23 |
| 09 Air flow $q_v$             | m <sup>3</sup> /h | 430  |
| 09 Pressure increase $p_{fs}$ | Pa                | 727  |
| 10 Speed (rpm) n              | min <sup>-1</sup> | 2695 |
| 11 Specific ratio*            |                   | 1.01 |

\* Specific ratio =  $1 + p_{fs} / 100\,000\text{ Pa}$

LU-56385



# AC centrifugal fan

forward-curved, single-intake  
with housing (flange)

## Technical description



|  |  |
|--|--|
| Weight   | 5.4 kg   |
| Fan size   | 180 mm   |
| Rotor surface  | Unpainted  |
| Terminal box material  | Die-cast aluminum  |
| Impeller material  | Sheet steel, galvanized  |
| Housing material   | Die-cast aluminum  |
| Direction of rotation  | Clockwise, viewed toward rotor   |
| Degree of protection   | IP44; installation- and position-dependent   |
| Insulation class   | "F"  |
| Moisture (F) / Environmental (H) protection class                          | F1-1   |
| Ambient temperature note   | Occasional start-up between -40°C and -25°C is permissible.<br>For continuous operation at temperatures below -25°C (e.g. refrigeration applications) we recommend our fan design with special low-temperature bearings. |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C  |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C  |
| Installation position  | Any  |
| Condensation drainage holes  | None   |
| Mode   | S1   |
| Motor bearing  | Ball bearing   |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA  |
| Electrical hookup  | Via terminal box   |
| Protection class   | I (with customer connection of protective earth)   |
| Conformity with standards  | EN 60335-1; CE   |
| Approval   | CCC  |



# AC centrifugal fan


forward-curved, single-intake  
with housing (flange)

## Product drawing



- |   |  |
|---|--|
| 1 | Tightening torque $1.3 \pm 0.2$ Nm                                       |
| 2 | Cable diameter min. 4 mm, max. 10 mm, tightening torque $1.3 \pm 0.2$ Nm |

## Connection diagram




# AC centrifugal fan

forward-curved, single-intake

with housing (flange)

## Curves: Air performance 50 Hz Δ



Measurement: LU-22378-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | Wired | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub>    | P <sub>fs</sub> | q <sub>v</sub> | P <sub>fs</sub> |
|---|-------|-----|----|-------------------|----------------|------|-------------------|-----------------|----------------|-----------------|
|   |       | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | Pa              | cfm            | in. wg          |
| 1 | Δ     | 230 | 50 | 2370              | 420            | 1.12 | 775               | 300             | 455            | 1.20            |
| 2 | Δ     | 230 | 50 | 2485              | 373            | 1.04 | 680               | 500             | 400            | 2.01            |
| 3 | Δ     | 230 | 50 | 2580              | 321            | 0.91 | 585               | 650             | 345            | 2.61            |
| 4 | Δ     | 230 | 50 | 2680              | 260            | 0.77 | 465               | 750             | 275            | 3.01            |

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

