

AC centrifugal fan

forward-curved, single-intake

with housing (flange), for solid-fuel heating systems

G2E120-SA58-06 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	G2E120-SA58-06	
Motor	M2E052-CA	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Method of obtaining data		cs
Valid for approval/standard		CE
Speed (rpm)	min ⁻¹	2050
Power consumption	W	46
Current draw	A	0.21
Capacitor	μF	1.5
Capacitor voltage	VDB	400
Capacitor standard		S0 (CE)
Min. back pressure	Pa	50
Min. back pressure	inH ₂ O	0.2
Max. ambient temperature	°C	85
Starting current	A	0.26

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC centrifugal fan

forward-curved, single-intake

with housing (flange), for solid-fuel heating systems

Technical description

Weight	1.86 kg
Fan size	120 mm
Rotor surface	Partly cast in aluminum
Impeller material	Sheet steel, hot-dip galvanized
Housing material	Die-cast aluminum
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP00
Insulation class	"F"
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Electrical hookup	Via terminal box, capacitor integrated and connected
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Motor capacitor according to EN 60252-1 in safety protection class	S0
Conformity with standards	EN 60335-1; CE




AC centrifugal fan

forward-curved, single-intake

with housing (flange), for solid-fuel heating systems

Product drawing




1	Terminal box open
1.1	green/yellow
1.2	brown + capacitor
1.3	black + capacitor
1.4	blue
2	Tightening torque 1.7 ± 0.25 Nm n<700 rpm

AC centrifugal fan

forward-curved, single-intake
with housing (flange), for solid-fuel heating systems

Connection diagram



N	blue	L	black	PE	green/yellow
---	------	---	-------	----	--------------




AC centrifugal fan

forward-curved, single-intake

with housing (flange), for solid-fuel heating systems

Curves: Air performance 50 Hz



Measurement: LU-53469-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH2O
1	230	50	2050	46	0.21	190	50	110	0.20
2	230	50	2265	42	0.18	155	160	90	0.64
3	230	50	2450	38	0.17	115	240	65	0.96
4	230	50	2575	36	0.16	70	300	40	1.20

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

