

AC centrifugal fan

forward-curved, single-intake
with housing (without flange)

G2E133-DN79-38 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	G2E133-DN79-38		
Motor	M2E068-BF		
Phase		1~	1~
Nominal voltage	VAC	115	115
Frequency	Hz	60	60
Method of obtaining data		fa	fa
Valid for approval/standard		CE	UL 2111
Speed (rpm)	min ⁻¹	2000	2000
Power consumption	W	101	105
Current draw	A	0.88	0.89
Capacitor	μF	8	8
Capacitor voltage	VDB	220	220
Capacitor standard		S0 (CE)	UL
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	40	40
Starting current	A	0.94	0.94

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC centrifugal fan

forward-curved, single-intake
with housing (without flange)

Technical description


Weight	1.8 kg
Fan size	133 mm
Rotor surface	Unpainted
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Axial
Protection class	I (with customer connection of protective earth)
Motor capacitor according to EN 60252-1 in safety protection class	S0
Conformity with standards	EN 60335-1; CE
Approval	UL 2111; CSA C22.2 No. 77



AC centrifugal fan

forward-curved, single-intake
with housing (without flange)

Product drawing




1	Cable PVC AWG20, 3-pole connector housing Tyco 350766-4, 2x plug pin Tyco 350538-1 and 1x plug pin Tyco 926885-1
1.1	L (blue)
1.2	Z (brown + capacitor)
1.3	N (black + capacitor)
2	Flat push-on receptacle 6.3 x 0.8, lockable
2	PE (green/yellow)

AC centrifugal fan

forward-curved, single-intake
with housing (without flange)

Connection diagram




U1	blue	Z	brown	U2	black
PE	green/yellow				



AC centrifugal fan

forward-curved, single-intake
with housing (without flange)

Curves: Air performance 60 Hz



Measurement: LU-67255-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	115	60	2000	101	0.88	220	0	130	0.00
2	115	60	2210	97	0.84	195	119	115	0.48
3	115	60	2465	94	0.81	160	241	95	0.97
4	115	60	2765	89	0.77	115	366	65	1.47

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

