

AC centrifugal fan

forward-curved, single-intake
with housing (flange)

G2E160-AL19-56 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	G2E160-AL19-56	
Motor	M2E068-GA	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Method of obtaining data		ml
Valid for approval/standard		CE
Speed (rpm)	min ⁻¹	2300
Power consumption	W	270
Current draw	A	1.2
Capacitor	µF	6
Capacitor voltage	VDB	400
Capacitor standard		S2 (CE)
Min. back pressure	Pa	300
Min. back pressure	inH ₂ O	1.2
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	55

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	33	33
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		44	44
05 Variable speed drive		No	

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_e	kW	0.18
09 Air flow q_v	m ³ /h	385
09 Pressure increase p_{fs}	Pa	549
10 Speed (rpm) n	min ⁻¹	2635
11 Specific ratio*		1.01

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-37599



AC centrifugal fan

forward-curved, single-intake
with housing (flange)

Technical description


Weight	4.7 kg
Fan size	160 mm
Rotor surface	Painted black
Impeller material	Sheet aluminum, painted black
Housing material	Die-cast aluminum, painted black
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP00; installation- and position-dependent
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H0+
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
Protection class	I (if protective earth is connected by customer to the housing's connection point)
Conformity with standards	EN 60335-1; CE



AC centrifugal fan


forward-curved, single-intake
with housing (flange)

Product drawing



- 1 Cable silicone 3x 0.5 mm², 3x crimped splices
- 2 Ground connection point 1/4"

Connection diagram




U1	blue	Z	brown	U2	black
----	------	---	-------	----	-------



AC centrifugal fan

forward-curved, single-intake
with housing (flange)

Curves: Air performance 50 Hz



Measurement: LU-37599-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	inH ₂ O
1	230	50	2300	270	1.20	565	300	335	1.20
2	230	50	2525	212	0.92	460	500	270	2.01
3	230	50	2655	175	0.76	360	575	210	2.31
4	230	50	2775	135	0.59	205	650	120	2.61

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

