

AC centrifugal fan

backward-curved, single-intake
with housing (without flange)

G2E225-AD54-10 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	G2E225-AD54-10		
Motor	M2E068-DF		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50	60
Method of obtaining data		ml	ml
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	2550	2650
Power consumption	W	135	190
Current draw	A	0.6	0.83
Capacitor	μF	3	3
Capacitor voltage	VDB	450	450
Capacitor standard		S2 (CE)	S2 (CE)
Min. back pressure	Pa	0	0
Min. back pressure	inH ₂ O	0	0
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	55	35
Starting current	A	1.06	1.01

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC centrifugal fan

backward-curved, single-intake
with housing (without flange)

Technical description


Weight	4.96 kg
Fan size	225 mm
Rotor surface	Unpainted
Impeller material	PA plastic
Housing material	Sheet steel, galvanized
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Axial
Protection class	I (with customer connection of protective earth)
Motor capacitor according to EN 60252-1 in safety protection class	S2
Conformity with standards	EN 60335-1; CE



AC centrifugal fan


backward-curved, single-intake
with housing (without flange)

Product drawing



1	Connector housing, Wago 723-604 / 018-042
1.1	blue
1.2	black + capacitor
1.3	green/yellow (PE)
1.4	not used

Connection diagram




N	blue	L	black	PE	Green/yellow
---	------	---	-------	----	--------------



AC centrifugal fan

backward-curved, single-intake
with housing (without flange)

Curves: Air performance 50 Hz



Measurement: LU-57172-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{ts}	q _v	p _{ts}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	230	50	2550	135	0.60	860	0	505	0.00
2	230	50	2500	140	0.61	660	200	385	0.80
3	230	50	2505	139	0.61	545	300	320	1.20
4	230	50	2560	132	0.57	380	450	225	1.81


U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{ts} = Pressure increase



AC centrifugal fan

backward-curved, single-intake
with housing (without flange)

Curves: Air performance 60 Hz



Measurement: LU-57171-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	inH ₂ O
1	230	60	2650	190	0.83	905	0	530	0.00
2	230	60	2605	191	0.83	745	150	440	0.60
3	230	60	2585	191	0.83	590	300	345	1.20
4	230	60	2800	177	0.77	330	600	195	2.41

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

