

EC centrifugal module

backward curved

with housing

G3G125-AA20-01 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Muldingen
County court Stuttgart · HRA 590344General partner Elektrobau Muldingen GmbH · Headquarters Muldingen
County court Stuttgart · HRB 590142

Nominal data

Type	G3G125-AA20-01	
Motor	M3G074-BF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	208 .. 250
Frequency	Hz	50/60
Type of data definition		ml
Speed	min ⁻¹	13000
Power input	W	530
Current draw	A	2.5
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations




Technical features

Mass	3.9 kg
Size	125 mm
Surface of rotor	Coated in black
Material of impeller	Aluminium sheet
Number of blades	6
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 20; Depending on installation and position
Insulation class	"B"
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	<ul style="list-style-type: none"> - Motor current limit - PFC, active - Soft start - Control input 0-10 VDC / PWM - Over-temperature protected electronics / motor
EMC interference immunity	Acc. to EN 61000-6-2
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-4 (industrial environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	With plug
Motor protection	Locked-rotor protection
Approval	VDE; UL 507; CSA C22.2 Nr.113

EC centrifugal module

backward curved
with housing

Product drawing




1	Connector housing Molex 39-01-2105
1.1	GND
1.2	PWM
1.3	PE
1.4	N
1.5	L




Connection screen

Customer circuit




Connection

Fan / motor



No.	Pin	Signal	Function / assignment
	1	GND	Reference ground for control interface, SELV
	2	PWM	PWM control input, 250-1250 Hz, Isink max 10 mA, SELV
	3	PE	Protective earth
	4	N	Neutral conductor
	5	L	Power supply 208-250 VAC, 50/60 Hz, phase

Charts: Air flow 50 Hz



Measurement: LU-51285
Measurement: LU-51040

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebmpapst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	Stage	U	f	n	P _{ed}	I	qv	P _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa
1	vo	230	50	13130	568	2.47	90	5061
2	vo	230	50	13090	566	2.46	70	9819
3	vo	230	50	13420	529	2.30	45	13120
4	vo	230	50	13880	471	2.05	30	15170
5	po	230	50	13000	575	2.50	90	5047
6	po	230	50	13000	600	2.60	70	10020
7	po	230	50	13090	568	2.47	50	14020
8	po	230	50	13520	512	2.23	30	16930

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · qv = Air flow · P_{fs} = Pressure increase

