

EC centrifugal fan

backward curved, single inlet
with housing (flange)

G3G126-AE11-10 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	G3G126-AE11-10	
Motor	M3G055-AI	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Type of data definition		ml
Speed (rpm)	min ⁻¹	5370
Power input	W	83
Current draw	A	0.73
Min. back pressure	Pa	0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



EC centrifugal fan

backward curved, single inlet
with housing (flange)

Technical features


Mass	1.8 kg
Size	126 mm
Surface of rotor	Thick layer passivated
Material of protective cover	PA plastic
Material of impeller	PA plastic
Housing material	Die-cast aluminium
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"B"
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None, open rotor
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Tach output - Output limit - Motor current limit - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Over-temperature protected electronics / motor - Line undervoltage detection
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	With plug
Motor protection	Locked-rotor protection
Cable exit	Variable
Degree of soiling	3
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 61800-5-1; CE
Approval	UL 1004-7 + 60730; CSA C22.2 No.77



EC centrifugal fan

backward curved, single inlet
with housing (flange)

Product drawing




1	Connection line PVC AWG18 with connector housing 3-pole Wieland 96.032.4053.1
1.1	PE (green/yellow)
1.2	N (blue)
1.3	L (black)
2	Connection line PVC AWG22, 1x connector housing 4-pole Weidmüller SAIS-4-IDC M8 small
2.1	GND (blue)
2.2	PWM (yellow)
2.3	+10 V (red)
2.4	Tach (white)



EC centrifugal fan

backward curved, single inlet
with housing (flange)

Connection screen




No.	Conn.	Designation	Colour	Function / assignment
	CON10	L	black	Power supply 230 VAC, 50-60 Hz, see type plate for voltage range
	CON11	N	blue	Neutral conductor
	CON12	PE	green/yellow	Protective earth
	1	GND	blue	GND connection for control interface
	2	0-10V PWM	yellow	Control input 0-10 V or PWM, electrically isolated
	3	10 V / max. 1,1 mA	red	Voltage output 10 VDC 1.1 mA, electrically isolated, short-circuit-proof
	4	Tacho	white	Tach output: Open collector, 1 pulse per revolution, electrically isolated



EC centrifugal fan

backward curved, single inlet
with housing (flange)

Charts: Air flow 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-168456-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	inH ₂ O
1	230	50	5370	83	0.73	135	0	80	0.00
2	230	50	5595	80	0.71	115	400	65	1.61
3	230	50	5845	70	0.64	90	800	50	3.21
4	230	50	6000	56	0.52	60	1100	35	4.42
5	230	50	5000	70	0.61	125	0	75	0.00
6	230	50	5000	57	0.50	100	321	60	1.29
7	230	50	5000	44	0.40	75	588	45	2.36
8	230	50	5000	32	0.30	50	763	30	3.06
9	230	50	4000	36	0.31	100	0	60	0.00
10	230	50	4000	29	0.26	80	205	50	0.82
11	230	50	4000	23	0.20	60	376	35	1.51
12	230	50	4000	16	0.15	40	488	25	1.96
13	230	50	3000	15	0.13	75	0	45	0.00
14	230	50	3000	12	0.11	60	116	35	0.47
15	230	50	3000	10.0	0.09	45	212	25	0.85
16	230	50	3000	7.0	0.07	30	275	15	1.10

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

