

G3G133-DD11-02

# EC centrifugal fan

forward curved, single inlet  
with housing (without flange)



G3G133-DD11-02 ebmpapst Datasheet  
sales@fansco.com  
www.fansco.com

Limited partnership · Headquarters Muldingen  
County court Stuttgart · HRA 590344

General partner Elektrobau Muldingen GmbH · Headquarters Muldingen  
County court Stuttgart · HRB 590142

## Nominal data

Type	G3G133-DD11-02	
Motor	M3G055-BD	
Phase		1~
Nominal voltage	VAC	115
Frequency	Hz	50/60
Type of data definition		ml
State		prelim.
Speed	min <sup>-1</sup>	2000
Power input	W	42
Current draw	A	0.60
Min. back pressure	Pa	0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit  
Subject to alterations



# EC centrifugal fan

forward curved, single inlet  
with housing (without flange)

## Technical features

<b>Mass</b>	1.6 kg
<b>Size</b>	133 mm
<b>Material of impeller</b>	Hot-dip galvanized sheet steel
<b>Housing material</b>	Sheet steel, hot-galvanised
<b>Direction of rotation</b>	Clockwise, seen on rotor
<b>Type of protection</b>	IP 44; Depending on installation and position as per EN 60034-5
<b>Insulation class</b>	"B"
<b>Humidity class</b>	F3-1
<b>Max. permissible ambient motor temp. (transp./ storage)</b>	+ 80 °C
<b>Min. permissible ambient motor temp. (transp./storage)</b>	- 40 °C
<b>Mounting position</b>	Shaft horizontal or rotor on bottom; rotor on top on request
<b>Condensate discharge holes</b>	Rotor-side
<b>Operation mode</b>	S1
<b>Motor bearing</b>	Ball bearing
<b>Technical features</b>	<ul style="list-style-type: none"> <li>- Output 10 VDC, max. 1.1 mA</li> <li>- Tach output</li> <li>- Motor current limit</li> <li>- Soft start</li> <li>- Control input 0-10 VDC / PWM</li> </ul>
<b>Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)</b>	<= 3.5 mA
<b>Motor protection</b>	Thermal overload protector (TOP) wired internally
<b>Cable exit</b>	Variable
<b>Protection class</b>	I (if protective earth is connected by customer)
<b>Product conforming to standard</b>	EN 60335-1
<b>Approval</b>	GOST




G3G133-DD11-02

# EC centrifugal fan

forward curved, single inlet  
with housing (without flange)

## Product drawing




- |   |   |
|---|---|
| 1 | Connection line H03VV, 3x brass lead tips crimped |
| 2 | Connection line A03VV, 4x brass lead tips crimped |



# EC centrifugal fan

forward curved, single inlet  
with housing (without flange)

## Connection screen




Line	No.	Signal	Colour	Function / assignment
	1	PE	green/yellow	Protective earth
	2	L	brown	Power supply 115 VAC, 50-60 Hz, see type plate for voltage range
	3	N	blue	Neutral conductor
	4	GND	blue	GND - Connection for control interface
	5	Tach	white	Tach output: open collector, 1 pulse per revolution, electrically isolated
	6	10V/ max. 1,1mA	red	Voltage output 10 V/ 1.1 mA, electrically isolated
	7	0-10V PWM	yellow	Control input 0 - 10 V or PWM, electrically isolated



# EC centrifugal fan

forward curved, single inlet  
with housing (without flange)

## Charts: Air flow 50 Hz



Measurement: LU-73164

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: L<sub>wA</sub> measured as per ISO 13347 / L<sub>pA</sub> measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

	U	f	n	P <sub>ed</sub>	I	qv	P <sub>fs</sub>
	V	Hz	min <sup>-1</sup>	W	A	m <sup>3</sup> /h	Pa
1	115	50	2000	42	0.60	220	0
2	115	50	2125	37	0.55	190	100
3	115	50	2280	31	0.45	150	200
4	115	50	2460	23	0.35	100	280
5	115	50	1950	39	0.57	215	0
6	115	50	1950	29	0.43	175	84
7	115	50	1950	19	0.28	130	147
8	115	50	1950	11	0.17	80	176
9	115	50	1650	24	0.35	180	0
10	115	50	1650	17	0.26	150	60
11	115	50	1650	12	0.17	110	106
12	115	50	1650	6.9	0.10	65	126
13	115	50	1350	13	0.19	150	0
14	115	50	1350	9.5	0.14	120	40
15	115	50	1350	6.3	0.09	90	71
16	115	50	1350	3.8	0.06	55	84

U = Supply voltage · f = Frequency · n = Speed · P<sub>ed</sub> = Power input · I = Current draw · qv = Air flow · p<sub>fs</sub> = Pressure increase

