

EC centrifugal fan

forward-curved, single-intake
with housing (flange)

G3G146-ED19-18 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	G3G146-ED19-18	
Motor	M3G055-CF	
Nominal voltage	VDC	380
Nominal voltage range	VDC	370 .. 390
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	1930
Power consumption	W	110
Current draw	A	0.5
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Technical description


Weight	2.6 kg
Fan size	146 mm
Rotor surface	Thick-film passivated
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, painted black
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F3-1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Fault output (open collector) - Power limiter - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor
Motor protection	Locked-rotor protection
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Product drawing




- | | |
|---|--|
| 1 | Cable halogen-free, 4x 0.25 mm ² , 4x crimped splices |
| 2 | Cable halogen-free, 3G 0.5 mm ² , 3x flat push-on receptacle Stocko RSB 8100 F2.8-1, 3x insulator Stocko EH 657.100 |

EC centrifugal fan

forward-curved, single-intake

with housing (flange)

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
	CON10	+	brown	Supply connection, power supply +, voltage range see nameplate
	CON11	-	blue	Supply connection, power supply -, voltage range see nameplate
	CON12	PE	green/yellow	Ground connection
	3	+10 V	red	Fixed voltage output 10 VDC ±3 %, I _{max} = 10 mA, short-circuit-proof, power supply for ext. devices (e.g. pot), SELV
	2	0- 10V PWM	yellow	0-10 V / PWM control input, R _i = 100 kΩ, SELV
	1	GND	blue	Reference ground for control interface, SELV
	4	FG/FB	white	Fan good / fan bad: open collector, fan good = low, electrically isolated, I _{sink} max = 10 mA
				Attention! Device may only be operated with control unit 61423-1-0173. This is not included in scope of delivery.

EC centrifugal fan

forward-curved, single-intake

with housing (flange)

Curves: Air performance



Measurement: LU-156812-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	LpA _{in}	LwA _{in}	qv	p _{fs}	qv	p _{fs}
	V	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	CFM	inH2O
1	380	1930	110	0.50	64	71	545	0	320	0.00
2	380	2275	110	0.50	64	70	440	250	260	1.00
3	380	2760	110	0.50	65	71	315	500	185	2.01
4	380	3315	110	0.50	70	76	185	700	110	2.81

U = Power supply · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side · qv = Air flow
p_{fs} = Pressure increase

