

EC centrifugal fan

forward-curved, single-intake
with housing (flange)



G3G160-AD52-15 ebmpapst Datasheet
sales@fansco.com
www.fansco.com



Nominal data

Type	G3G160-AD52-15	
Motor	M3G074-BF	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2870
Power consumption	W	170
Current draw	A	1.2
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	43.7	32.8
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		54.9	44
05 Variable speed drive		Yes	

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_{ed}	kW	0.17
09 Air flow q_v	m ³ /h	395
09 Pressure increase p_{fs}	Pa	600
10 Speed (rpm) n	min ⁻¹	2870
11 Specific ratio*		1.01

* Specific ratio = $1 + p_s / 100\,000\text{ Pa}$

LU-72532



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Technical description


Weight	3.3 kg
Fan size	160 mm
Rotor surface	Unpainted
Impeller material	Sheet steel, galvanized
Housing material	Die-cast aluminum
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F3-1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on top; rotor on bottom on request
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Tach output - Motor current limitation - Soft start - Set value input Lin 0-10 VDC / PWM (1.7 V corresponds to V=min, 10 V corresponds to V=max) - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains
EMC immunity to interference	According to EN 61000-6-2
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	With plug
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Product drawing




1	Cable PVC 3G AWG18 and PVC 4X AWG22 with connector housing Sto-Lock EH 712-009-003-960
1.1	0-10 V / PWM (yellow)
1.2	tach output (white)
1.3	GND (blue)
1.4	+10V (red)
1.5	PE (green/yellow)
1.6	N (blue)
1.7	L (black)
2	Cable PVC 3G AWG18 and PVC 4X AWG22 with connector housing Sto-Lock EH 713-009-003-960, length 1800mm, included separately



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
	2	L	black	Power supply 230 VAC, 50-60 Hz, see nameplate for voltage range
	3	N	blue	Neutral conductor
	1	PE	green/yellow	Protective earth
	7	0-10 V PWM	yellow	Control input 0-10 V or PWM, electrically isolated
	5	Tach	white	Tach output: open collector, 1 pulse per revolution, electrically isolated
	6	10V / max 1.1 mA	red	Voltage output 10 V / 1 mA, electrically isolated
	4	GND	blue	GND connection for control interface

EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Curves: Air performance 50 Hz



Measurement: LU-72532-1
Measurement: LU-72533-1
Measurement: LU-72534-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

