

EC centrifugal fan

forward-curved, single-intake

with housing (flange)

G3G160-CN01-01 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	G3G160-CN01-01	
Motor	M3G055-DF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1625
Power consumption	W	85
Current draw	A	0.7
Min. back pressure	Pa	0
Min. back pressure	in. wg	0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Technical description


Weight	2.9 kg
Fan size	160 mm
Rotor surface	Unpainted
Impeller material	PA plastic
Housing material	Die-cast aluminum
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from supply - Thermal overload protection for electronics/motor
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 55022 (class B, household environment), the application may require ferritic damping in the cable due to the conditions of installation.
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Electronic motor protection
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE



EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Product drawing



- | | |
|---|-------------------------------------|
| 1 | Cable PVC AWG20, 3x crimped splices |
| 2 | Cable PVC AWG22, 4x crimped splices |




EC centrifugal fan

forward-curved, single-intake

with housing (flange)

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
	CON10	L	black	Power supply 230 VAC, 50-60 Hz, see nameplate for voltage range
	CON11	N	blue	Neutral conductor
	CON12	PE	green/yellow	Protective earth
	1	GND	blue	GND connection for control interface
	2	0- 10V PWM	yellow	Control input 0-10 V or PWM, electrically isolated
	3	10V/ max 1.1mA	red	Voltage output 10 V / 1.1 mA, electrically isolated, not short-circuit-proof
	4	Tach	white	Tach output: Open collector, 1 pulse per revolution, electrically isolated, I _{sink} max = 10 mA

EC centrifugal fan

forward-curved, single-intake
with housing (flange)

Curves: Air performance 50 Hz



Measurement: LU-138971-1
Measurement: LU-138973-1
Measurement: LU-138977-1
Measurement: LU-138978-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	230	50	1625	85	0.70	65	71	500	0	295	0.00
2	230	50	1890	82	0.68	62	69	405	200	240	0.80
3	230	50	2190	74	0.64	62	69	295	360	175	1.45
4	230	50	2380	56	0.50	63	70	170	420	100	1.69
5	230	50	1550	71	0.61			475	0	280	0.00
6	230	50	1690	58	0.52			360	160	210	0.64
7	230	50	1830	44	0.43			245	249	145	1.00
8	230	50	1960	33	0.34			140	279	80	1.12
9	230	50	1220	35	0.36			370	0	220	0.00
10	230	50	1310	28	0.30			280	94	165	0.38
11	230	50	1405	21	0.24			185	142	110	0.57
12	230	50	1475	16	0.20			105	154	60	0.62
13	230	50	860	13	0.17			260	0	155	0.00
14	230	50	910	11	0.15			190	44	110	0.18
15	230	50	960	8.9	0.13			125	65	75	0.26
16	230	50	1000	7.4	0.11			70	68	40	0.27

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{fs} = Pressure increase

