

# EC centrifugal fan - RadiCal

backward-curved, single-intake

with housing (flange)

G3G190-RQ23-15 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

## Nominal data

|                          |                   |            |
|--------------------------|-------------------|------------|
| Type                     | G3G190-RQ23-15    |            |
| Motor                    | M3G055-CF         |            |
| Phase                    |                   | 1~         |
| Nominal voltage          | VAC               | 230        |
| Nominal voltage range    | VAC               | 200 .. 240 |
| Frequency                | Hz                | 50/60      |
| Method of obtaining data |                   | ml         |
| Speed (rpm)              | min <sup>-1</sup> | 3400       |
| Power consumption        | W                 | 100        |
| Current draw             | A                 | 0.9        |
| Min. ambient temperature | °C                | -25        |
| Max. ambient temperature | °C                | 60         |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change




## Technical description

|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight                                                                     | 2.1 kg                                                                                                                                                                                                                                                                                                                                                                            |
| Size                                                                       | 190 mm                                                                                                                                                                                                                                                                                                                                                                            |
| Motor size                                                                 | 55                                                                                                                                                                                                                                                                                                                                                                                |
| Rotor surface                                                              | Thick-film passivated                                                                                                                                                                                                                                                                                                                                                             |
| Impeller material                                                          | PA plastic                                                                                                                                                                                                                                                                                                                                                                        |
| Housing material                                                           | PP plastic                                                                                                                                                                                                                                                                                                                                                                        |
| Number of blades                                                           | 7                                                                                                                                                                                                                                                                                                                                                                                 |
| Direction of rotation                                                      | Clockwise, viewed toward rotor                                                                                                                                                                                                                                                                                                                                                    |
| Degree of protection                                                       | IP20                                                                                                                                                                                                                                                                                                                                                                              |
| Insulation class                                                           | "B"                                                                                                                                                                                                                                                                                                                                                                               |
| Moisture (F) / Environmental (H) protection class                          | H0+                                                                                                                                                                                                                                                                                                                                                                               |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                                                                                                                                                                                                                                                                                                                                           |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                                                                                                                                                                                                                                                                                                                                           |
| Installation position                                                      | Any                                                                                                                                                                                                                                                                                                                                                                               |
| Condensation drainage holes                                                | None, open rotor                                                                                                                                                                                                                                                                                                                                                                  |
| Mode                                                                       | S1                                                                                                                                                                                                                                                                                                                                                                                |
| Motor bearing                                                              | Ball bearing                                                                                                                                                                                                                                                                                                                                                                      |
| Technical features                                                         | <ul style="list-style-type: none"> <li>- Power limiter</li> <li>- Motor current limitation</li> <li>- RS-485 MODBUS-RTU</li> <li>- Soft start</li> <li>- Control interface with SELV potential safely disconnected from the mains</li> <li>- Overvoltage detection</li> <li>- Thermal overload protection for electronics/motor</li> <li>- Line undervoltage detection</li> </ul> |
| EMC immunity to interference                                               | According to EN 61000-6-1 (household environment)                                                                                                                                                                                                                                                                                                                                 |
| EMC circuit feedback                                                       | According to EN 61000-3-2/3                                                                                                                                                                                                                                                                                                                                                       |
| EMC interference emission                                                  | According to EN 61000-6-3 (household environment)                                                                                                                                                                                                                                                                                                                                 |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | <= 3.5 mA                                                                                                                                                                                                                                                                                                                                                                         |
| Motor protection                                                           | Electronic motor protection                                                                                                                                                                                                                                                                                                                                                       |
| Protection class                                                           | I (with customer connection of protective earth)                                                                                                                                                                                                                                                                                                                                  |
| Conformity with standards                                                  | EN 60335-1; CE                                                                                                                                                                                                                                                                                                                                                                    |

# EC centrifugal fan - RadiCal

backward-curved, single-intake  
with housing (flange)

## Product drawing




|     |                                                                                                                                                                                    |
|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | 4-pole connector housing JST XARR-04V, 3x plug pin JST SXAM-01T-P0.6                                                                                                               |
| 1.1 | GND (blue)                                                                                                                                                                         |
| 1.2 | RSA (white)                                                                                                                                                                        |
| 1.3 | RSB (brown)                                                                                                                                                                        |
| 1.4 | not used                                                                                                                                                                           |
| 2   | 3-pole connector housing tyco 2005250-1, 3x plug pin tyco 177917-1                                                                                                                 |
| 2.1 | PE (green/yellow)                                                                                                                                                                  |
| 2.2 | N (blue)                                                                                                                                                                           |
| 2.3 | L (black)                                                                                                                                                                          |
| 3   | Tapping hole prepared for self-tapping screw for fastening plastics (Remform) dia. 4 mm, clearance for screw max. 15 mm. The torque is to be determined on the basis of the screw. |
| 4   | 5x sheet metal nut for thread EN ISO 1478-ST4.8 (max. screw length 16 mm plus thickness of mounting material)                                                                      |
| 5   | Connecting sleeve not suitable for installation with pipe clamps                                                                                                                   |

# EC centrifugal fan - RadiCal

backward-curved, single-intake  
with housing (flange)

## Connection diagram




| No.    | Conn. | Designation | Color        | Function/assignment                                              |
|--------|-------|-------------|--------------|------------------------------------------------------------------|
| CON10  | 1     | L           | black        | Power supply, phase, see nameplate for voltage range             |
| CON11  | 1     | N           | blue         | Power supply, neutral conductor, see nameplate for voltage range |
| CON12  | 1     | PE          | green/yellow | Protective earth                                                 |
| CON130 | 3     | RSB         | brown        | RS485 interface for MODBUS, RSB; SELV                            |
| CON130 | 2     | RSA         | white        | RS485 interface for MODBUS, RSA; SELV                            |
| CON130 | 1     | GND         | blue         | Reference ground for control interface, SELV                     |



# EC centrifugal fan - RadiCal

backward-curved, single-intake  
with housing (flange)

## Curves: Air performance



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-188033-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | Wired | U   | f  | n                 | P <sub>ed</sub> | I    | q <sub>v</sub> | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|---|-------|-----|----|-------------------|-----------------|------|----------------|-----------------|----------------|-----------------|
|   |       | V   | Hz | min <sup>-1</sup> | W               | A    | m³/h           | Pa              | cfm            | in. wg          |
| 1 | 1~    | 230 | 50 | 3515              | 96              | 0.88 | 695            | 0               | 410            | 0.00            |
| 2 | 1~    | 230 | 50 | 3400              | 100             | 0.90 | 515            | 300             | 305            | 1.20            |
| 3 | 1~    | 230 | 50 | 3495              | 98              | 0.90 | 350            | 550             | 205            | 2.21            |
| 4 | 1~    | 230 | 50 | 3610              | 89              | 0.82 | 220            | 700             | 130            | 2.81            |


Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>ed</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase



# EC centrifugal fan - RadiCal

backward-curved, single-intake  
with housing (flange)

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-188033-1  
Measurement: LU-188107-1  
Measurement: LU-188109-1  
Measurement: LU-188112-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

