

AC centrifugal fan

forward-curved, single-intake

with housing (large flange), for rail applications

G4D180-CD28-21 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	G4D180-CD28-21		
Motor	M4D068-EC		
Phase		3~	3~
Nominal voltage	VAC	400	400
Wiring		Y	Y
Frequency	Hz	50	60
Method of obtaining data		fa	ml
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	1250	1420
Power consumption	W	220	245
Current draw	A	0.38	0.4
Min. back pressure	Pa	0	120
Min. back pressure	inH ₂ O	0	0.48
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	75	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · oe = Customer equipment
Subject to change



AC centrifugal fan

forward-curved, single-intake

with housing (large flange), for rail applications

Technical description

Weight	5.9 kg
Fan size	180 mm
Rotor surface	Painted black
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent as per EN 60034-5
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F2-2
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on top; rotor on bottom on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1, motor does not have factory-installed overheating protection; CE




AC centrifugal fan

forward-curved, single-intake

with housing (large flange), for rail applications

Product drawing




1 Cable halogen-free, BETrans® 3 GKW flex, sw 6G 0.5 mm², 6x crimped splices

AC centrifugal fan

forward-curved, single-intake
with housing (large flange), for rail applications

Connection diagram



Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2x gray
PE	green/yellow				




AC centrifugal fan

forward-curved, single-intake

with housing (large flange), for rail applications

Curves: Air performance 50 Hz



Measurement: LU-41517-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH2O
1	400	50	1250	220	0.38	1190	0	700	0.00
2	400	50	1300	182	0.33	1045	70	615	0.28
3	400	50	1350	147	0.29	875	140	515	0.56
4	400	50	1410	101	0.25	590	210	345	0.84

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase




AC centrifugal fan

forward-curved, single-intake

with housing (large flange), for rail applications

Curves: Air performance 60 Hz



Measurement: LU-41518-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH2O
1	400	60	1420	245	0.40	1040	120	615	0.48
2	400	60	1500	203	0.34	920	190	540	0.76
3	400	60	1560	171	0.30	800	240	470	0.96
4	400	60	1620	138	0.26	640	280	380	1.12

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

