

AC centrifugal fan

forward-curved, single-intake

with housing (large flange)

G4D200-CD04-26 ebmpapst Datasheet

sales@fansco.com

www.fansco.com



Nominal data

Type	G4D200-CD04-26		
Motor	M4D068-GA		
Phase		3~	3~
Nominal voltage	VAC	400	400
Wiring		Y	Y
Frequency	Hz	50	60
Method of obtaining data		fa	fa
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	1370	1530
Power consumption	W	210	310
Current draw	A	0.47	0.54
Min. back pressure	Pa	0	0
Min. back pressure	inH ₂ O	0	0
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	80	65

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · oe = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	33.6	32.3	09 Power consumption P_e	kW	0.14
02 Measurement category		A		09 Air flow q_v	m ³ /h	700
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	243
04 Efficiency grade N		45.3	44	10 Speed (rpm) n	min ⁻¹	1420
05 Variable speed drive		No		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-109697



AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Technical description


Weight	7.8 kg
Fan size	200 mm
Rotor surface	Unpainted
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized, with light-gray powder coating (RAL 7035)
Fan housing material	Sheet steel, galvanized and coated with light gray plastic (RAL 7035)
Guard grille material	Steel, galvanized
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F1-1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	UL 1004-1; CSA C22.2 No. 100



AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Product drawing




1 Cable PFA AWG20 (green/yellow AWG18), 6x crimped splices

AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Connection diagram



Change of rotation direction by reversing two phases


	Three-phase motor
Y	Star connection
1	Counterclockwise operation
L1	= V1 = blue
L2	= U1 = black
L3	= W1 = brown
2	Clockwise operation
L1	= U1 = black
L2	= V1 = blue
L3	= W1 = brown
PE	green/yellow
TOP	2x gray



AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Curves: Air performance 50 Hz



Measurement: LU-117882-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH2O
1	Y	400	50	1370	210	0.47	1020	0	600	0.00
2	Y	400	50	1410	167	0.42	810	120	475	0.48
3	Y	400	50	1435	133	0.40	610	200	360	0.80
4	Y	400	50	1455	101	0.39	375	240	220	0.96


Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase



AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Curves: Air performance 60 Hz



Measurement: LU-117883-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH2O
1	Y	400	60	1530	310	0.54	1145	0	675	0.00
2	Y	400	60	1595	255	0.46	955	140	565	0.56
3	Y	400	60	1650	198	0.39	745	260	435	1.04
4	Y	400	60	1710	132	0.32	430	340	255	1.36

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

